


SAW Bandpass Filter 260401B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512


Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	260401B	
		Rev. Date	2006-08-07	
		Rev.	NW6007-CS01	1/5

SAW Bandpass Filter 260401B



3. Specifications

Fo = 240.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	239.85	240.0	240.15
Insertion Loss	dB	-	23.5	27.5
1dB Bandwidth	MHz	4.0	4.3	-
3dB Bandwidth	MHz	-	4.48	-
40dB Bandwidth	MHz	-	5.3	5.4
Amplitude Ripple (Fo +/- 1.875 MHz)	dB	-	0.6	1.0
Group Delay Variation (Fo +/- 1.875 MHz)	nsec	-	105	250
Absolute Delay	usec	-	2.92	-
Ultimate Rejection	dB	45	50	
Temperature Coefficient of Frequency	ppm/°C ²	-	-0.03	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	260401B	
		Rev. Date	2006-08-07	
		Rev.	NW6007-CS01	2/5

SAW Bandpass Filter 260401B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)




L1 = 18 nH, L2 = 15 nH

5. Marking Configuration

ITF¹⁾ 06A001²⁾
260401B³⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	260401B	
		Rev. Date	2006-08-07	
		Rev.	NW6007-CS01	3/5

SAW Bandpass Filter 260401B







6. Typical Performance (at +25°C)



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	260401B	
		Rev. Date	2006-08-07	
		Rev.	NW6007-CS01	4/5

SAW Bandpass Filter 260401B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809

Part No. 260401B

Rev. Date 2006-08-07

Rev. NW6007-CS01 5/5