

APPLICATION

Home, Small Office, POS, Internet Bar

FEATURES

- Compact size
- Excellent microprocessor control guarantees high reliability
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function

PHASE (ONLY FOR ONLINE UPS)

Phase: 1-phase in / 1-phase out

INPUT

Capacity: 800 VA / 480 W
Voltage: 220/230/240 VAC
Voltage Range: 180-290 VAC62
Frequency Range: 60/50 Hz (auto sensing)

OUTPUT

AC Voltage Regulation (Batt. Mode) : ±10%
Frequency Range (Batt. Mode): 60 Hz or 50 Hz ±1 Hz
Transfer Time: Typical 2 ~ 6 ms,
Waveform (Batt. Mode): Simulated Sine Wave

BATTERY

Battery Type: 12 V/7 Ah
Battery Number: 1
Typical Recharge Time: 4-6 hours up to 90% capacity



SAFETY STANDARD APPAOVAL



PROTECTION

Full Protection: Overload, Discharge, and Overcharge Protection

PHYSICAL

Output Receptacles: India, French, Schuko, NEMA, and IEC ions
Dimension: 279mm(L) x 101mm(W) x 142mm(H)
Net Weight (kgs): 4.2

OPERATING ENVIRONMENT

Humidity: 0-90 % RH @ 0- 40°C (non-condensing)
Noise Level: Less than 40dB

MANAGEMENT

Optional USB/RS-232 Port: Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC 8

This content is subject to change, please refer to specification for more detail.
 FSP reserve the right to change the content without prior notice