

DIELECTRIC RESONATOR OSCILLATOR

Model 512133

2000 - 3000 MHz

Features

- Low Noise Bipolar Transistor
- Rugged Construction for Extreme Environmental Conditions
- High Frequency Stability
- Mechanically Tuned

Specifications

CHARACTERISTIC	TYPICAL Ta = +25 °C	MIN/MAX Ta = -55°C to +85 °C
Frequency	2000 - 3000 MHz	2000 - 3000 MHz
Output Power (dBm)	+13.0	+10.0 Min.
Power Flatness (dBm)	+/- 1.5	+/- 3.0
Frequency Stability (ppm)/ °C	4	3 to 5
Harmonics (dBc)	-20	-15 Max.
Spurious (dBc)	-80	-80 Max.
Phase Noise (2000 MHz) @ 100 KHz (dBc/Hz)	-132	-130 Max.
Load VSWR	1.5:1	2.0:1 Max.
Power	Vdc mA	+15 to +20 90 Max.





Absolute Maximum (No Damage) Ratings

Ambient Operating Temperature -55°C to +100 °C
Storage Temperature -62°C to +125 °C
Case Temperature +125 °C
DC Voltage +24 Volts
Maximum DC Tuning Voltage +20 Volts
Minimum DC Tuning Voltage 0 Volts

NOTE: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data

Phase Noise	Typical	Typical
Offset	2000 MHz	3000 MHz
1 kHz	-93	-91
10 kHz	-115	-112
100 kHz	-132	-131



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 Rev. 5/5/10

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001