



- NOTES:
1. ALL DIMENSION IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
 5. CONTACT RATING (NON-SWITCHING): 5 Amps
 6. CIRCUIT: 6 POSITIONS, 60° INDEX, CONTINUOUS ROTATION.
 7. NO HARDWARE SUPPLIED.
 8. OPERATING FORCE: 425±100 Grams/cm
 9. OPERATING TEMP.: -30°C to 85°C
 10. DIELECTRIC STRENGTH: 1000 V RMS min. @sea level
 11. DESIGNATE MAJOR DIMENSIONS
 12. TERMINAL ARE GOLD FLASH OVER SILVER



REV.	ECN NO.	DESCRIPTION	DATE	CHKD	TITLE	SCALE	DATE	DR	DWG	REV
B	11206	REMOVED EPOXY	1/23/01	CJB	KC60-RANCD N-P-F W/ D WASHER HOLES	1.5:1	1/23/01	CJB	G000001	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED