

	1	2	3	4	5	6	7																																																																
A								A																																																															
B								B																																																															
C								C																																																															
D								D																																																															
E								E																																																															
F								F																																																															
G	<p style="text-align: center;">RoHS compliant</p>							G																																																															
H	<table border="1"> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> <td>7</td> </tr> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>XX</td> <td>±0.3</td> <td></td> <td></td> <td>Drawn</td> <td>14.12.2007</td> <td>N.Schulz</td> </tr> <tr> <td>XXX</td> <td>±0.2</td> <td>④</td> <td>Change of the plant</td> <td>Approved</td> <td>17.12.2012</td> <td>Wranke</td> </tr> <tr> <td>X.XXX</td> <td>±0.1</td> <td>③</td> <td>Update</td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>Update</td> <td>08.07.2009</td> <td></td> <td>Dean</td> </tr> <tr> <td>Ang.</td> <td>±3°</td> <td>①</td> <td>Drawn</td> <td>14.12.2007</td> <td></td> <td>N.Schulz</td> </tr> <tr> <td>UNIT</td> <td>mm</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> </tr> </table>							1	2	3	4	5	6	7	Scale	1:1						TOLERANCE							XX	±0.3			Drawn	14.12.2007	N.Schulz	XXX	±0.2	④	Change of the plant	Approved	17.12.2012	Wranke	X.XXX	±0.1	③	Update				DIM	TOL	②	Update	08.07.2009		Dean	Ang.	±3°	①	Drawn	14.12.2007		N.Schulz	UNIT	mm	Id.	Modification	Date	Name		H
1	2	3	4	5	6	7																																																																	
Scale	1:1																																																																						
TOLERANCE																																																																							
XX	±0.3			Drawn	14.12.2007	N.Schulz																																																																	
XXX	±0.2	④	Change of the plant	Approved	17.12.2012	Wranke																																																																	
X.XXX	±0.1	③	Update																																																																				
DIM	TOL	②	Update	08.07.2009		Dean																																																																	
Ang.	±3°	①	Drawn	14.12.2007		N.Schulz																																																																	
UNIT	mm	Id.	Modification	Date	Name																																																																		
<table border="1"> <tr> <td>Customer-No.</td> <td>ASSMANN WSWI-No.</td> <td>Drawing-No.</td> <td>Replace</td> </tr> <tr> <td></td> <td>A-KGB-S</td> <td>ASS 0889E CO</td> <td>rev04</td> </tr> </table>							Customer-No.	ASSMANN WSWI-No.	Drawing-No.	Replace		A-KGB-S	ASS 0889E CO	rev04																																																									
Customer-No.	ASSMANN WSWI-No.	Drawing-No.	Replace																																																																				
	A-KGB-S	ASS 0889E CO	rev04																																																																				
<p>NOTES:</p> <p>A. Material: 1. Housing: PA66 UL 94V-0 2. Terminal: COPPER ALLOY, TIN PLATED</p> <p>B. Electrical Characteristics: 1. Rating: 15A 250V~ (UL,CUL) 10A 250V~ (CCC VDE) 2. Electric Strength: AC 2.000 V FOR ONE MINUTE 3. Insulation Resistance: 100MΩ MIN. AT 500V DC C. Approvals: UL, CUL, CCC, VDE</p>																																																																							
<p style="text-align: center;">ASSMANN <small>WSWI components</small></p>																																																																							
<p style="text-align: center;">190</p>																																																																							