

General Cable Product Data Sheet

Part Number: C3241

Revision Level: 1

Date: 10/26/2007

2C 16 SOLID BC HALAR PVC

Fire Alarm/Life Safety Cable

A. CONSTRUCTION

Conductor: #16 AWG Solid Bare Copper
Insulation: 0.016" Wall Halar
Cable: 2C @ 4.00" LHL
Jacket: 0.015" Wall FLEXGUARD* - Red
Print Legend: *E86522-F CAROL CABLE TYPE FPLP 16 AWG -- C3241 -- (UL) -- MID-CAP ---(seq. Footage*

DIAMETERS

0.051" nom.
0.083" nom.
0.166" nom.
0.196" +/- 0.01"

mkgs every 2 ft. in ascending order) i.e. 000003, 000006, etc.

B. INDUSTRY APPROVALS

National Electrical Code Article 760
UL Standard 1424 Type FPLP

C. ELECTRICAL PROPERTIES

TEMPERATURE: 75C
SUGGESTED WORKING VOLTAGE (V_{rms}): 300V
CONDUCTOR D.C. RESISTANCE: 4.2 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.