

Asymmetric Dual N- Channel Enhancement Mode MOSFET


MTNN081404SH8

	Tr 1	Tr 2
BV_{DSS}	40V	40V
$I_D@V_{GS}=10V, T_A=25^\circ C$	9.8A	12A
$I_D@V_{GS}=10V, T_C=25^\circ C$	44A	65A
$R_{DS(on)(typ)}@V_{GS}=10V$	9.8m Ω	6.3m Ω
$R_{DS(on)(typ)}@V_{GS}=4.5V$	14.3m Ω	8.0m Ω


Features

- Simple drive requirement
- Low on-resistance
- Fast switching speed
- Pb-free lead plating and halogen-free package

Equivalent Circuit




Outline



Ordering Information

Device	Package	Shipping
MTNN081404SH8-0-T6-G	DFN 5 x 6 (Pb-free lead plating & halogen-free package)	3000 pcs / Tape & Reel





Absolute Maximum Ratings (T_C=25°C, unless otherwise noted)

Parameter	Symbol	Limits		Unit	
		Tr 1	Tr 2		
Drain-Source Breakdown Voltage	BV _{DSS}	40	40	V	
Gate-Source Voltage	V _{GS}	±20	±20		
Continuous Drain Current	I _D	TA=25 °C, VGS=10V	9.8	12	A
		TA=70 °C, VGS=10V	7.8	9.6	
		TC=25 °C, VGS=10V	44	65	
		TC=100 °C, VGS=10V	27.8	41	
Pulsed Drain Current (Note 1 & 2)	I _{DM}	88	130		
Single Pulse Avalanche Current @ L=0.1mH	I _{AS}	20	40		
Single Pulse Avalanche Energy (Note 4)	E _{AS}	20	80	mJ	
Power Dissipation	P _{DSM}	TA=25 °C (Note 3)	2.01	2.08	W
		TA=70 °C (Note 3)	1.2	1.3	
	P _D	TC=25 °C	48	69	
		TC=100 °C	19	27	
Operating Junction and Storage Temperature Range	T _j ; T _{stg}	-55~+150		°C	

Thermal Data

Parameter	Symbol	Value		Unit
Thermal Resistance, Junction-to-case, max	R _{θJC}	2.6	1.8	°C/W
Thermal Resistance, Junction-to-ambient, max	R _{θJA}	62	60	
Thermal Resistance, Junction-to-ambient, max (Note 3)		27	25	

- Note :
1. Pulse width limited by maximum junction temperature
 2. Duty cycle ≤ 1%
 3. Surface mounted on 1 in² copper pad of FR-4 board, t ≤ 10s; 125°C/W when mounted on minimum copper pad.
 4. For Tr 1, 100% tested by conditions of L=0.5mH, V_{DD}=15V, V_{GS}=10V, I_{AS}=5A; for Tr 2, 100% tested by conditions of L=0.5mH, V_{DD}=15V, V_{GS}=10V, I_{AS}=12A

Tr 1, Electrical Characteristics (T_C=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	40	-	-	V	V _{GS} =0V, I _D =250μA
V _{GS(th)}	1.0	-	2.5		V _{DS} =V _{GS} , I _D =250μA
I _{GSS}	-	-	±100	nA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	1	μA	V _{DS} =32V, V _{GS} =0V
	-	-	25		V _{DS} =30V, V _{GS} =0V, T _j =125°C
*R _{DS(ON)}	-	9.8	14	mΩ	V _{GS} =10V, I _D =12A
	-	14.3	19.5		V _{GS} =4.5V, I _D =10A
*G _{FS}	-	7.8	-	S	V _{DS} =10V, I _D =5A



Dynamic					
Ciss	-	708	-	pF	V _{DS} =20V, V _{GS} =0V, f=1MHz
Coss	-	107	-		
Crss	-	55	-		
*td(ON)	-	8.4	-	ns	V _{DS} =20V, I _D =12A, V _{GS} =10V, R _G =1Ω
*tr	-	13	-		
*td(OFF)	-	25.6	-		
*tf	-	7.4	-		
*Qg(V _{GS} =10V)	-	14.6	-	nC	V _{DS} =20V, I _D =12A, V _{GS} =10V
*Qg(V _{GS} =4.5V)	-	7.3	-		
*Qgs	-	2	-		
*Qgd	-	4	-		
Body Diode					
*V _{SD}	-	0.73	1	V	V _{GS} =0V, I _S =1A
*trr	-	10.8	-	ns	I _F =6A, dI _F /dt=100A/μs
*Qrr	-	4.6	-	nC	


*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

Tr 2, Electrical Characteristics (T_c=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	40	-	-	V	V _{GS} =0V, I _D =-250μA
V _{GS(th)}	1.0	-	2.5		V _{DS} =V _{GS} , I _D =-250μA
I _{GSS}	-	-	±100	nA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	1	μA	V _{DS} =32V, V _{GS} =0V
	-	-	25		V _{DS} =30V, V _{GS} =0V, T _j =125°C
*R _{D(S)ON}	-	6.3	8	mΩ	V _{GS} =10V, I _D =12A
	-	8.0	12		V _{GS} =4.5V, I _D =10A
*G _{FS}	-	11.4	-	S	V _{DS} =10V, I _D =7A
Dynamic					
Ciss	-	1466	-	pF	V _{DS} =20V, V _{GS} =0V, f=1MHz
Coss	-	178	-		
Crss	-	117	-		
*td(ON)	-	13.6	-	ns	V _{DS} =20V, I _D =12A, V _{GS} =10V, R _G =1Ω
*tr	-	15.4	-		
*td(OFF)	-	43.2	-		
*tf	-	8.2	-		
*Qg(V _{GS} =10V)	-	31.2	-	nC	V _{DS} =20V, I _D =12A, V _{GS} =10V
*Qg(V _{GS} =4.5V)	-	15.9	-		
*Qgs	-	5.3	-		
*Qgd	-	7.2	-		
Body Diode					
*V _{SD}	-	0.72	1	V	V _{GS} =0V, I _S =1A
*trr	-	15	-	ns	I _F =12A, dI _F /dt=100A/μs
*Qrr	-	8.2	-	nC	

*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

Recommended Soldering Footprint




unit : mm




Typical Characteristics : Q1(N-channel)


Typical Output Characteristics




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics(Cont.) : Q1(N-channel)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature






Typical Characteristics(Cont.) : Q1(N-channel)


Single Pulse Power Rating, Junction to Ambient
 (Note on page 2)



Typical Transfer Characteristics




Transient Thermal Response Curves






Typical Characteristics : Q2(N-channel)


Typical Output Characteristics




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Source Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics(Cont.) : Q2(N-channel)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics(Cont.) : Q2(N-channel)


Single Pulse Power Rating, Junction to Ambient
 (Note on page 2)




Typical Transfer Characteristics




Transient Thermal Response Curves



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

DFN5x6 Dimension



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.90	1.10	0.035	0.043	F	2.55	2.90	0.100	0.114
b	0.33	0.51	0.013	0.020	H	0.61	0.81	0.024	0.032
C	0.20	0.30	0.008	0.012	I	1.10	1.30	0.043	0.051
D1	4.80	5.00	0.189	0.197	J	0.40	0.60	0.016	0.024
D2	3.61	3.96	0.142	0.156	K	0.50	-	0.020	-
E	5.90	6.10	0.232	0.240	L	0.51	0.71	0.020	0.028
E1	5.70	5.80	0.224	0.228	L1	0.06	0.20	0.002	0.008
E2	2.02	2.42	0.080	0.095	α	0°	12°	0°	12°
\square	1.27 BSC		0.050 BSC						

Notes: 1.Controlling dimension: millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.