



Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female

TECHNICAL DATA SHEET

PE831R1020

The PE831R1020 is a dual junction isolator offering 36 dB minimum of isolation over a frequency band of 4 to 8 GHz. This coaxial part uses type N female connectors on all ports and has a power rating of 10 watts in forward and 2 watts in reverse direction.

Pasternack Enterprises offers a wide variety of isolators to fit your needs. These are two-port devices that transmit microwave or radio frequency power in one direction only and block the signal in the opposite direction. They can be thought of as a diode for RF energy. Isolators are used to isolate equipment from the effects of conditions outside of the equipment. For instance they are used to prevent a microwave source being detuned by a mismatched load. Pasternack's isolators feature excellent insertion loss, high isolation and reliability.

- Dual Junction Isolator
- Frequency Range of 4 to 8 GHz
- Female N Connectors
- Low VSWR

Applications

- Radar Systems
- Military
- Wireless Radio Systems
- Telecom Infrastructure
- Communication Systems
- R&D Labs
- Microwave Radio Systems

Configuration

| | |
|-----------------|----------------|
| Connector 1 | N Female |
| Connector 2 | SMA Female |
| Frequency Range | 4 GHz to 8 GHz |
| Design | Dual Junction |
| Layout | Connectorized |

Electrical Specifications (Values at 25°C, sea level)

| Description | Minimum | Typical | Maximum | Units |
|-----------------|---------|---------|---------|-------|
| Frequency Range | 4 | | 8 | GHz |
| Impedance | | 50 | | Ohms |
| Insertion Loss | | | 1 | dB |
| Forward Power | | | 10 | Watts |
| Reverse Power | | | 2 | Watts |
| Input VSWR | | | 1.3:1 | |
| Isolation | 36 | | | dB |

Mechanical Specifications

Temperature

Operating Range 0 to 50 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female PE831R1020](#)



Dual Junction Isolator With 36 dB Isolation From
4 GHz to 8 GHz, 10 Watts And N Female

TECHNICAL DATA SHEET

PE83IR1020

Size

| | |
|--------|---------------------|
| Length | 2 in [50.8 mm] |
| Width | 0.63 in [16 mm] |
| Height | 1.25 in [31.75 mm] |
| Weight | 0.23 lbs [104.33 g] |

Compliance Certifications (visit www.Pasternack.com for current document)

| | |
|-----------------|------------|
| RoHS Compliant | |
| REACH Compliant | 12/17/2015 |

Plotted and Other Data

Notes:

- Values at 25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female PE83IR1020](#)





Dual Junction Isolator With 36 dB Isolation From
4 GHz to 8 GHz, 10 Watts And N Female

TECHNICAL DATA SHEET

PE83IR1020

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female PE83IR1020](#)






Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female

TECHNICAL DATA SHEET

PE83IR1020



Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female PE83IR1020](http://www.pasternack.com/dual-junction-isolator-36db-isolation-8-ghz-10-watts-n-female-pe83ir1020-p.aspx)

URL: <http://www.pasternack.com/dual-junction-isolator-36db-isolation-8-ghz-10-watts-n-female-pe83ir1020-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE83IR1020 CAD Drawing

Dual Junction Isolator With 36 dB Isolation From 4 GHz to 8 GHz, 10 Watts And N Female



DWG TITLE

PE83IR1020

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 050616

SCALE N/A

SIZE A

2233

(PE) PASTERNAK
 THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com