

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0785650001](#)
Status: **Active**
Overview: [DDR3 DIMM Sockets](#)
Description: 1.00mm Pitch Aerodynamic DDR3 DIMM Socket, Low Profile, Vertical, Surface Mount, Black Housing and Latches, 0.76µm Gold (Au Plating, 3.18mm PCB Thickness, 240 Circuits, Lead-Free

Documents:

[3D Model](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Drawing \(PDF\)](#)

Agency Certification

CSA LR19980
 UL E29179

General

Product Family Memory Module Sockets
 Series [78565](#)
 Component Type Socket
 Electrical Model Yes
 JEDEC Outline SO-014
 Overview [DDR3 DIMM Sockets](#)
 Product Name DDR3 DIMM
 UPC 884982367661

Physical


Circuits (Loaded) 240
 Circuits (maximum) 240
 Color - Resin Black
 Durability (mating cycles max) 25
 Entry Angle Vertical
 Flammability 94V-0
 Keying to Mating Part Yes
 Material - Metal Copper Alloy
 Material - Plating Mating Gold
 Material - Plating Termination Tin
 Material - Resin Nylon
 Net Weight 6.807/g
 PCB Locator Yes
 PCB Retention Yes
 PCB Thickness - Recommended 3.18mm
 Packaging Type Tray
 Pitch - Mating Interface 1.00mm
 Pitch - Termination Interface 1.00mm
 Plating min - Mating 0.762µm
 Plating min - Termination 2.540µm
 Temperature Range - Operating -55°C to +85°C
 Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.0A
 Voltage - Maximum 30V AC (RMS)/DC
 Voltage Key Center

Solder Process Data

Duration at Max. Process Temperature (seconds) 040
 Lead-freeProcess Capability REFLOW
 Max. Cycles at Max. Process Temperature 002



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Contains SVHC(2015 June 15): No

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
 Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

China RoHS

Green Image

Not Relevant

Search Parts in this Series

[78565 Series](#)

Mates With

JEDEC Standard 1.27mm Modules

Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Electrical Model Document	EE-78565-001
S-Parameter Model	SP-78565-001
Sales Drawing	SD-78565-001

This document was generated on 10/29/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION