


TYPE: _____ QUANTITY: _____ PROJECT: _____

CATALOG NUMBER:

FIXTURE WATTAGE VOLTAGE FINISH OPTION OPTION OPTION OPTION



- 1- Heavy cast aluminum top cover with integral LED heat dissipating pad.
- 2- One piece .090" (2.3) thick hard aluminum top shade. Underside surface is painted white enamel to optimize light performance (EC613 only).
- 3- Set of three aluminum louvers.
- 4- Set of 4 X 1/2" (13) solid aluminum struts.
- 5- High impact white translucent UV stabilized acrylic diffuser.
- 6- Cast aluminum upper electrical housing.
- 7- Cast aluminum lower electrical chamber housing.

EC612



EC612-EC6WS



EC613



EC613-EC6W



MATERIALS

Eclipse Mini is made of corrosion resistant 356 aluminum alloy with a copper (CU) content of less than 0.1%. Light source is enclosed in a high impact white translucent UV stabilized acrylic sealed diffuser. Increased impact protection with a set of aluminum louvers. The lower cast aluminum housing fits with a 4" or 5" (102 or 127) pole and contains all electrical controls on a removable tray.

ELECTRICAL

LED

DRIVER Standard driver is 0-10V dimming-ready (dims to 10%) with: 120-277 multi-volt compatibility (50-60Hz), optional 347V on request, minimum operating temperature of -30°C/-22°F, output over voltage protection, output over current protection, output short circuit protection with auto-recovery, and over temperature protection (110°C).

LED Standard 4000K/80CRI. Optional 2700K, 3000K and 3500K. Removable modular LED platform.

LIFE

60,000hrs $L_{60B_{50}}$ (based on IESNA TM-21 Test Method and LM-80 data).
139,000hrs $L_{70B_{50}}$ (calculated projection from LM-80 data).

FINISH



Five-stage preparation process includes preheating of cast aluminum parts for air extraction. Polyester powder coating is applied through an electrostatic process, and oven cured for long term finish.

MOUNTING

Maximum weight: 9.11lbs (4.13kg)
Standard luminaire mounts on a 4" (102) or 5" (127) pole.
Alternate wall and pole attachments are proposed with high quality components to meet multiple installation conditions.


CERTIFICATION

Tested to UL1598 and CSA 22.2 #250. ETL listed wet location. Photometric testing performed by an independent laboratory in accordance with IES LM-79-08 standards at 25°C. Lumen depreciation in accordance with IESNA LM80 standards. CE certification on request. Rated IP65.



EC612/EC613 SERIES ECLIPSE MINI - LED

TYPICAL PHOTOMETRY SUMMARY



Descriptive Information

EC612-L1W48r0
EC613-L1W48r0

Total Lms: 2528 Lumens
Total Input Watts: 49.6 W
Source: LED
Efficacy: 51.0 Lumens/Watt
BUG: B1-U3-G2
CCT/CRI: 4000K/80
Maximum Candela: 345 @ 65°V

Please visit our web site www.luminis.com for complete I.E.S. formatted download data.

LUMINAIRE SELECTION

MODEL#	LED LIGHT SELECTION (4000K/80CRI)	VOLTAGE ¹	FINISH
 <input type="checkbox"/> EC612	SUFFIX <input type="checkbox"/> L1W18r1 <input type="checkbox"/> L1W30r1 <input type="checkbox"/> L1W48r0	INPUT WATTS 19W 34W 50W	DELIVERED LUMENS 1057 1818 2528
	<input type="checkbox"/> 120V <input type="checkbox"/> 277V Optional <input type="checkbox"/> 347V	STANDARD COLORS <input type="checkbox"/> WHT Snow white <input type="checkbox"/> BKT Jet black <input type="checkbox"/> BZT Bronze <input type="checkbox"/> MST Matte silver <input type="checkbox"/> GRT Titanium gray <input type="checkbox"/> DGT Gun metal <input type="checkbox"/> CHT Champagne	
 <input type="checkbox"/> EC613			OPTIONAL COLORS <input type="checkbox"/> CS Custom color <input type="checkbox"/> RAL RAL# color (Refer to color chart)

OPTIONS

ELECTRICAL	MOUNTING	ACCESSORIES
<input type="checkbox"/> FS Fuse ² <input type="checkbox"/> PH Photocell ² <input type="checkbox"/> 347L 347V input power driver	<input type="checkbox"/> AC6 Pole mount attachment with 45° support <input type="checkbox"/> 2AC6 Double pole mount attachments with 45° support at 180° <input type="checkbox"/> AW6 Wall mount attachment with 45° support <input type="checkbox"/> EC6P Pole mount attachment with arm <input type="checkbox"/> 2EC6P Double pole mount attachment with arms at 180° <input type="checkbox"/> EC6W Wall mount attachment with arm <input type="checkbox"/> EC6PS Pole mount attachment with short arm (EC612 only) <input type="checkbox"/> 2EC6PS Double pole mount attachment with short arms at 180° (EC612 only) <input type="checkbox"/> EC6WS Wall mount attachment with short arm (EC612 only) <input type="checkbox"/> TN3 3" Tenon pole adaptor ³ <input type="checkbox"/> PR6 Pedestal mount adaptor	<input type="checkbox"/> HS6 House side shield

NOTES

- 1- If no voltage is specified, luminaires are factory prewired by default for 120V. For other voltages, please specify with catalog number, or consult factory.
- 2- Fuse and photocell options are normally installed with poles when specified with Luminis luminaires. (Except for other types of mounting.)
- 3- 3" tenon pole adaptor only required for 3" O.D. poles by others.

LUMINIS®








LUMINIS | Toll free: 866.586.4647 Fax: 514.683.8872
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

LUMINIS.COM

Luminaires may be altered for design improvement or discontinued without prior notice.

EC612/EC613 SERIES ECLIPSE MINI - LED

POLE MOUNT




NOTE: PST pole with AC6 or 2AC6 attachment requires a 30" (762) tenon extension over pole nominal height. EC6P, 2EC6P, EC6PS and 2EC6PS require an 18" tenon extension. Factory installed.

MATCHING POLE SELECTION

Ø 4"	Ø 5"	Ø 4"	Tapered Pole	Ø 4"	Height
PAA410	PAA510	PST10	-----	PSB10	10 Ft. (3 M)
PAA412	PAA512	PST12	-----	PSB12	12 Ft. (3,6 M)
PAA414	PAA514	PST14	-----	PSB14	14 Ft. (4,2 M)
PAA416	PAA516	PST16	PTA16	PSB16	16 Ft. (4,8 M)
PAA418	PAA518	-----	PTA18	PSB18	18 Ft. (5,5 M)
PAA420	PAA520	-----	PTA20	PSB20	20 Ft. (6,0 M)
-----	-----	-----	PTA25	-----	25 Ft. (7,6 M)

For additional pole details, please refer to separate pole specification sheet.
Ø 4"= 102mm Ø5"= 127mm



June 2017 Rev 0



EC612/EC613 SERIES ECLIPSE MINI - LED

WALL MOUNT

AW6
1" X 2" (25X51) extruded aluminum extended arm wall mounting adaptor with cast aluminum covers and galvanized steel mounting plates. 1/2" dia. X 45° standard natural stainless steel rod support.

Mounting

EC6W (Applicable for EC612 and EC613)
1" X 2" (25X51) extruded aluminum wall mount arm with cast aluminum wall plate.

Mounting

EC6WS (Applicable for EC612 only)
1" X 2" (25X51) extruded aluminum wall mount arm with cast aluminum wall plate.

Mounting

