

KSD1616-Y/G/L

KSD1616A-Y/G

NPN Silicon Epitaxial Transistors

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Audio frequency power amplifier & medium speed switching
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: D1616 X

Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	KSD1616	50
		KSD1616A	60
V_{CBO}	Collector-Base Voltage	KSD1616	60
		KSD1616A	120
V_{EBO}	Emitter-Base Voltage	6.0	V
I_C	Collector Current (DC)	1.0	A
I_{CP}	Collector Current (Pulse) ⁽¹⁾	2.0	A
P_C	Collector power dissipation	0.75	W
T_J	Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
--------	-----------	-----	-----	-----	-------

OFF CHARACTERISTICS

I_{CBO}	Collector Cutoff Current ($V_{CB}=60Vdc, I_E=0$)	---	---	100	nAdc
I_{EBO}	Emitter-Base Cutoff Current ($V_{EB}=6.0Vdc, I_C=0$)	---	---	100	nAdc

ON CHARACTERISTICS


h_{FE-1}	DC Current Gain ($I_C=100mAdc, V_{CE}=2.0Vdc$)	KSD1616	135	---	600	---
		KSD1616A	135	---	400	---
h_{FE-2}	DC Current Gain ($V_{CE}=2.0Vdc, I_C=1.0Adc$)	81	---	---	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ⁽²⁾ ($I_C=1.0Adc, I_B=50mAdc$)	---	0.15	0.3	Vdc	
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ⁽²⁾ ($I_C=1.5Adc, I_B=75mAdc$)	---	0.9	1.2	Vdc	
$V_{BE(ON)}$	Base-Emitter On Voltage ⁽²⁾ ($V_{CE}=2.0Vdc, I_C=50mAdc$)	600	640	700	mVdc	
f_T	Current Gain Bandwidth Product ($I_C=100mAdc, V_{CE}=2.0Vdc$)	100	160	---	MHz	
C_{ob}	Collector Output Capacitance ($V_{CE}=10Vdc, I_E=0, f=1.0MHz$)	---	19	---	pF	
T_{ON}	Turn On Time	$V_{CC}=10V,$ $I_C=100mA,$ $I_{B1}=I_{B2}=10mA,$ $V_{BE(off)}=2\sim 3V$	---	0.07	---	us
t_{STG}	Storage Time		---	0.95	---	us
T_F	Fall Time		---	0.07	---	us

$h_{FE(1)}$ Classification

Classification	Y	G	L
h_{FE-1}	135-270	200-400	300-600

(1) PW<10ms, Duty Cycle<50%

(2) Pulse Test: PW<350us, Duty Cycle<2% Pulsed



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.175	.185	4.45	4.70	
B	.175	.185	4.45	4.70	
C	.500	---	12.70	---	
D	.016	.020	0.41	0.63	
E	.135	.145	3.43	3.68	
G	.095	.105	2.42	2.67	Straight Lead
	.173	.220	4.40	5.60	Bent Lead

* For ammo packing detailed specification, click here to visit our website of product packaging for details.



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-AP	Ammo Packing: 20Kpcs/Carton
Part Number-BP	Bulk: 100Kpcs/Carton

Note : Adding "-HF" suffix for halogen free, eg. Part Number-AP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com