



SMB Jack Bulkhead Mount Connector Crimp/  
Solder Attachment for RG178, RG196

RF Connectors Technical Data Sheet

PE4364

**RG178, RG196**

- SMB Jack Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry

- RG178, RG196 Interface Type
- Crimp/Solder Attachment
- Bulkhead

**2 GHz**

- Max. Operating Frequency 2 GHz
- Good VSWR of 1.5:1

- Gold Plated Brass Contact
- 30 µin minimum contact plating

**General Purpose Test**

- General Purpose Test

- Rack and Panel Mount Applications

- Custom Cable Assemblies



Pasternack's PE4364 SMB jack bulkhead connector with crimp/solder attachment for RG178 and RG196 is part of our full line of RF components available for same-day shipping. Our SMB jack connector operates up to a maximum frequency of 2 GHz and offers good VSWR of 1.5:1. This SMB bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assemblies for you and ship same-day.

**Operating Voltage (AC)**

HVFULSWLRQ	0LQPR	7SLFDO	0D[LPR	8QVV
Frequency Range	DC		2	GHz
VSWR			1.5:1	
Operating Voltage (AC)			250	Vrms

**Dimensions**

6LJH	
Length	0.845 in [21.46 mm]
Width/Dia.	0.237 in [6.02 mm]
Weight	0.001 lbs [0.45 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, [SMB Jack Bulkhead Mount Connector Crimp/Solder Attachment for RG178, RG196 PE4364](#)





