


Features

- Isolation voltage 3500 V~
- Industrial Standard Package
- High Surge Capability
- Glass Passivated Chips
- Simple Mounting
- Electrically Isolated by DBC Ceramic



Applications

- DC Motor Control and Drives
- Battery Charges
- Welders
- Power Converters
- Lighting Control
- Heat and Temperature Control



Advantages

- Space and weight savings
- Improved temperature and power cycling

ABSOLUTE MAXIMUM RATINGS

 $T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Test Condition	Value	Unit
V_{RRM}		1600	V
$I_{T(AV)}$	$T_C=85^\circ\text{C}$, 180° conduction, half sine wave;	130	A
$I_{T(RMS)}$	as AC switch;	300	A
I_{TSM}	$T_J=45^\circ\text{C}$, $t=10\text{ms}$ (50Hz), sine, $V_R=0$;	3200	A
	$T_J=45^\circ\text{C}$, $t=8.3\text{ ms}$ (60Hz), sine, $V_R=0$;	3360	
	$T_J=45^\circ\text{C}$, $t=10\text{ms}$ (50Hz), sine, $V_R=V_{RRM}$;	2700	
	$T_J=45^\circ\text{C}$, $t=8.3\text{ ms}$ (60Hz), sine, $V_R=V_{RRM}$;	2800	
I^2t	$T_J=45^\circ\text{C}$, $t=10\text{ms}$ (50Hz), sine, $V_R=0$;	52	KA^2s
	$T_J=45^\circ\text{C}$, $t=8.3\text{ ms}$ (60Hz), sine, $V_R=0$;	57	
	$T_J=45^\circ\text{C}$, $t=10\text{ms}$ (50Hz), sine, $V_R=V_{RRM}$;	37	
	$T_J=45^\circ\text{C}$, $t=8.3\text{ ms}$ (60Hz), sine, $V_R=V_{RRM}$;	39	
I_{DRM}/I_{RRM}	$T_J=125^\circ\text{C}$, $V_D=V_R=1600\text{V}$;	50	mA
dV/dt	$T_J=125^\circ\text{C}$, exponential to 67% rated V_{DRM}	1000	V/us
V_{ISOL}	50Hz, all terminals shorted, $t=1\text{s}$, $I_{ISOL}\leq 1\text{mA}$;	3500	V~
T_J	Max. junction operating temperature range	-40~125	
T_{STG}	Max. storage temperature range	-40~150	°C

ELECTRICAL CHARACTERISTICS $T_C=25^\circ C$ unless otherwise specified

Symbol	Test Condition	Min.	Typ.	Max.	Unit
V_{TO}	$16.7\% \times \pi \times I_{AV} < I < \pi \times I_{AV}, T_J = 130^\circ C;$			0.86	V
	$I > \pi \times I_{AV}, T_J = 130^\circ C;$			1.05	V
r_t	$16.7\% \times \pi \times I_{AV} < I < \pi \times I_{AV}, T_J = 130^\circ C;$			2.02	$m\Omega$
	$I > \pi \times I_{AV}, T_J = 130^\circ C;$			1.65	$m\Omega$
I_H	$V_{AK}=6V$, initial $I_T=30A$;			200	mA
I_L	Anode supply =6V, resistive load=1 Ω , gate pulse =10V, 100us;			400	mA
V_{TM}	$I_{TM}=408A$, $t_d=10$ ms, half sine;		1.57		V
P_{GM}	$t_p \leq 5ms$, $T_J=125^\circ C$;			12	W
$P_{GM(AV)}$	$f=50Hz$, $T_J=125^\circ C$;			3	W
I_{GM}	$t_p \leq 5ms$, $T_J=125^\circ C$;			3	A
$-V_{GT}$				10	V
V_{GT}	$V_A=6V$, $R_A=1\Omega$, $T_J=-40^\circ C$;			4	V
	$V_A=6V$, $R_A=1\Omega$;			2.5	
	$V_A=6V$, $R_A=1\Omega$, $T_J=125^\circ C$;			1.7	
I_{GT}	$V_A=6V$, $R_A=1\Omega$, $T_J=-40^\circ C$;			270	A
	$V_A=6V$, $R_A=1\Omega$;			150	
	$V_A=6V$, $R_A=1\Omega$, $T_J=125^\circ C$;			80	
V_{GD}	$V_{AK}=V_{DRM}$, $T_J=125$			0.3	V
I_{GD}				10	mA
di/dt	$I_{TM}=400A$, rated V_{DRM} , $T_J=125$			300	A/us

THERMAL AND MECHANICAL CHARACTERISTICS $T_C=25^\circ C$ unless otherwise specified

Symbol	Test Condition	value	Unit
R_{thjc}	DC operation, per junction;	0.20	K/W
R_{THCS}	Mounting surface smooth, flat and greased, per junction;	0.1	K/W
M_d	Mounting torque(M6)	4 to 6	$N\cdot m$
	Terminal connection torque(M6)		
Weight	Typical value	156	g

Characteristic curves




Figure 1. current rating characteristics




Figure 2. current rating characteristics




Figure 3. on-state power loss characteristics




Figure 4. on-state power loss characteristics




Figure 5. Maximum Non-Repetitive Surge Current









Figure 6. Maximum Non-Repetitive Surge Current



MIMMK130S160UA

Package Outline (Dimensions in mm)

