



Dual 1 Form A
Solid State Relay



DESCRIPTION

The AD4C101 is a bi-directional, double-pole, single-throw, normally open MOSFET output solid-state relay. This device offers two discrete optically isolated SSRs in one miniature 8 pin DIP/SMD package. Each discrete relay consists of an infrared LED, optically coupled to a Photo Diode Array, which in turn drives a pair of back-to-back MOSFETs. Its high blocking voltage (600V) and the integration of 2 devices in one package make the AD4C101 ideal in applications with board space constraints where high load voltages are encountered.

FEATURES

- High Blocking Voltage (600V)
- Two discrete relays in compact 8 pin DIP/SMD package
- High Input-Output Isolation (3.75kV)
- 120mA Continuous Load Current (each pole, individually)
- On-Resistance 40 ohms MAX
- Long Life / High Reliability
- Lead-Free / RoHS - WEEE Compliant

APPLICATIONS

- EMR replacement
- Meter Reading Systems
- Medical Equipment
- Battery Monitoring
- Multiplexers

OPTIONS/SUFFIXES*

- -S Surface Mount Leadform Option (50pcs / tube)
- -TR Tape & Reel Packing Option (1,000pcs/reel)


NOTE: Suffixes listed above are not included in marking on device for part number identification.

ABSOLUTE MAXIMUM RATINGS*

PARAMETER	UNIT	MIN	TYP	MAX
Storage Temperature	°C	-55		125
Operating Temperature	°C	-40		85
Continuous Input Current	mA			40
Transient Input Current	mA			400
Reverse Input Control Voltage	V	6		
Output Power Dissipation	mW			800

*The values indicated are absolute stress ratings. Functional operation of the device is not implied at these or any conditions in excess of those defined in electrical characteristics section of this document. Exposure to Absolute Ratings may cause permanent damage to the device and may adversely affect reliability.

SCHEMATIC DIAGRAM









APPROVALS

- UL / C-UL Approved: File # E90096, E201932
- CSA Approved: Certificate # LR111581-1

ELECTRICAL CHARACTERISTICS - 25°C


PARAMETER	UNIT	MIN	TYP	MAX	TEST CONDITIONS
INPUT SPECIFICATIONS					
LED Forward Voltage	V		1.8	2	If = 10mA
LED Reverse Voltage	V		0.5		Ir = 10uA
Turn-On Current	m A		1.75	5	Io = 120mA
Turn-Off Current	m A	0.2			
OUTPUT SPECIFICATIONS					
Blocking Voltage	V	600			Io = 1uA
Continuous Load Current	m A			120	If = 5mA, each pole, individually
On-Resistance	Ω		30	40	Io = 120mA
Leakage Current	μ A		0.2	1	Vo = 600V
Output Capacitance	p F	6			If = 0, f = 1.0MHz
Offset Voltage	m V			0.2	If = 5mA
COUPLED SPECIFICATIONS					
Isolation Voltage	V	3750			T = 1 minute
Turn-On Time	m s		0.75	5	If = 5mA, Io = 120mA
Turn-Off Time	m s		0.05	2	If = 0mA, Io = 120mA
Isolation Resistance	G Ω	100			
Coupled Capacitance	p F		3		
Contact Transient Ratio	V / μ s	2000	7000		dV = 50V

PERFORMANCE DATA




MECHANICAL DIMENSIONS


8 PIN DUAL IN-LINE PACKAGE



END VIEW




TOP VIEW




**BOTTOM VIEW/
BOARD PATTERN**


8 PIN SURFACE MOUNT DEVICE



END VIEW



TOP VIEW



**BOTTOM VIEW/
BOARD PATTERN**

DISCLAIMER

Solid State Optronics (SSO) makes no warranties or representations with regards to the completeness and accuracy of this document. SSO reserves the right to make changes to product description, specifications at any time without further notice. SSO shall not assume any liability arising out of the application or use of any product or circuit described herein. Neither circuit patent licenses nor indemnity are expressed or implied. Except as specified in SSO's Standard Terms & Conditions, SSO disclaims liability for consequential or other damage, and we make no other warranty, expressed or implied, including merchantability and fitness for particular use.

LIFE SUPPORT POLICY

SSO does not authorize use of its devices in life support applications wherein failure or malfunction of a device may lead to personal injury or death. Users of SSO devices in life support applications assume all risks of such use and agree to indemnify SSO against any and all damages resulting from such use. Life support devices are defined as devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when used properly in accordance with instructions for use can be reasonably expected to result in significant injury to the user, or (d) a critical component in any component of a life support device or system whose failure can be reasonably expected to cause failure of the life support device or system, or to affect its safety or effectiveness.