



## M Series

### Low Frequency Bandpass Filter

PC mountable or connector with lower loss, more complexity, and higher power.

#### Overview

	Standard Parameters	Special Parameters	Comments
Frequency Range	10 to 100 MHz	2 to 500 MHz	
Percentage Bandwidth	1 to 100%	0.5 to 200%	
Maximum VSWR	1.5:1	1.2:1	
Average Input Power	1 Watt	Up to 10 Watts	Measured up to 10,000 feet
Phase Linearity	± 5°	± 2°	
Phase Matching	± 2°	± 1°	
Maximum Attenuation	Up to 50 dBc	Up to 65 dBc	
Topology	Chebyshev	*Consult Factory	
Nominal Impedance	50 Ohms	**Consult Factory	
Number of Sections	6	12	
Shock	5 G's	Up to 500 G's	See Below
Vibration	5 G's	Up to 500 G's	See Below
Humidity	90%, non-condensing	Up to 100%, non-condensing	See Below
Altitude	Unlimited	Unlimited	See Below
Operating Temperature	0 to +50 °Celsius	-55 to +125 °Celsius	See Below
Storage Temperature	-55 to +85 °Celsius	-65 to +150 °Celsius	See Below
Gross Leak	As required	As required	Additional testing charges will apply
Fine Leak	As required	As required	Additional testing charges will apply
Moisure Resistance	100%	100%	
Dimensions	2.38" x 1.00" x 1.00"		
Mounting Options	PC Mount or Categorized		Gross and Fine Leak do not apply to connectorized parts.
	SMA Female or Male		



Connector Options	Standard Parameters	Special Parameters	Comments
		Type "N", BNC, TNC, SMC, or SMB Female or Male	

Other parameters may be specified. Please consult factory for any deviation from standard.

\*Other topologies are available upon request or design need. These can include, but are not limited to: Gaussian, Butterworth, Bessel, Elliptical, and Pole-placed designs.

\*\*Other impedances can be achieved, but the package is designed as a 50 Ohm unit. Matching to any other impedance will need prior approval and may not be guaranteed.

Any environmental testing will incur additional charges. Consult factory for costs associated with environmental testing. All filters can be "Designed to" and may not require the additional testing. Each application will be different.

**Need help now? Visit [Mtronpti.com](http://Mtronpti.com) and click...**

-  [Request a Quote](#)
-  [Find a Rep or Distributor](#)
-  [Contact](#)

**Orlando**

2525 Shader Rd  
Orlando, FL 32804 USA  
Phone: 407-298-2000  
Fax: 407-293-2979

**Shanghai**

Room 2215, 22/F  
Tomson Commercial Building  
710 Dongfang Road  
Pudong, Shanghai, China  
Phone: 86-21-6165-2282  
Fax: 86-21-6165-2283

**Yankton**

1703 E. Highway 50  
Yankton, SD 57078-0630 USA  
Phone: 605-665-9321  
Toll Free: 800-762-8800  
Fax: 605-665-1709

**Asia Pacific**

Unit 1108, 11<sup>th</sup> Floor, APEC Plaza  
48 Hoi Yuen Road  
Kwun Tong, Kowloon, Hong Kong, China  
Phone: 852-2866-8023  
Fax: 852-2529-1822

**India**

Noida  
SDF-D3 Zone (NSEZ) Special Economic  
Noida - 201305 (U.P.)  
New Delhi, India  
Phone 91-120-256-2014  
Fax: 91-120-256-3242

**Europe**

Bolwerk 26  
Veldhoven – 5509 MH  
Netherlands  
Phone: 31-40-368-6818  
Fax: 31-40-368-3501

MtronPTI may change specifications without notice to improve end application performance or product manufacturability. No liability is assumed as a result of product use or application. Please contact MtronPTI for latest information.

Copyright © 2014 MtronPTI