



PJEC2415VM1WS

ESD Protection

V_{RWM}

24V/15V

Features

- Bidirectional ESD protection of one line
- IEC61000-4-2(ESD): ±15kV Air, ±8kV Contact Compliance with the capability up to ±30kV
- IEC61000-4-4(EFT): 40A(5/50nS)
- IEC61000-4-5(Lightning): 3A(8/20μS)
- Low leakage current, maximum of 0.05μA at rated voltage
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std.
(Halogen Free)

Mechanical Data

- Case: SOD-323, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.00014 ounces, 0.0041 grams
- Marking: VM

Applications

- LIN-bus protection
- Automotive application

SOD-323

Unit : inch(mm)





Fig.130(TOP VIEW)



Cathode 1 (15V)
Cathode 2 (24V)

Maximum Ratings (T_A=25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Peak Pulse Power Dissipation(tp=8/20μs)	P _{PP}	160	W
ESD IEC61000-4-2(Air)	V _{ESD}	±30	kV
ESD IEC61000-4-2(Contact)		±30	
Operating Junction Temperature	T _J	-55 to +150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C



PJEC2415VM1WS

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage (24V)	V_{RWM}	-	-	-	24	V
Reverse Stand-Off Voltage (15V)		-	-	-	15	V
Reverse Breakdown Voltage (24V)	V_{BR}	$I_{BR}=5\text{mA}$	25.4	-	30.3	V
Reverse Breakdown Voltage (15V)			17.1	-	20.3	V
Reverse Leakage Current (24V)	I_R	$V_R=24\text{V}$	-	1	50	nA
Reverse Leakage Current (15V)		$V_R=15\text{V}$	-	1	50	
Clamping Voltage (24V)	V_{CL}	$I_{PP}=1\text{A}, t_P=8/20\mu\text{s}$	-	-	40	V
		$I_{PP}=3\text{A}, t_P=8/20\mu\text{s}$	-	-	50	
Clamping Voltage (15V)		$I_{PP}=1\text{A}, t_P=8/20\mu\text{s}$	-	-	25	
		$I_{PP}=5\text{A}, t_P=8/20\mu\text{s}$	-	-	35	
Off State Junction Capacitance	C_J	0Vdc Bias f=1MHz	-	13	17	pF



PJEC2415VM1WS

TYPICAL CHARACTERISTIC CURVES




Fig.1 Typical Junction Capacitance(24V)




Fig.2 Typical Junction Capacitance(15V)




Fig.3 Typical Peak Clamping Voltage(8/20µs)(24V)




Fig.4 Typical Peak Clamping Voltage(8/20µs)(15V)




Fig.5 8/20µs Pulse Waveform




Fig.6 Transmission Line Pulsing (TLP) Measurement




PJEC2415VM1WS

MOUNTING PAD LAYOUT

SOD-323

Unit : inch(mm)



ORDER INFORMATION

- Packing information
T/R – 12K per 13" plastic Reel
T/R – 5K per 7" plastic Reel



PJEC2415VM1WS

Part No_packing code_Version

PJEC2415VM1WS_R1_00001

PJEC2415VM1WS_R2_00001

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd -5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



PJEC2415VM1WS

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.