




LIGITEK

BACKLIGHT


L-02401G-B

SERIES


Package Dimension:



Note:1.All dimension are in millimeter tolerance is $\pm 0.25\text{mm}$ unless otherwise noted.
2.Specifications are subject to change without notice.



$$\Delta_{EH\%} = \frac{L(\text{MAX}) - L(\text{MIN})}{L(\text{MAX})} \times 100\%$$



Electrical/Optical Characteristics(Ta=25°C) Emitting Color:Green

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	TEST CONDITION
Luminous Intensity	IV	80	130	—	cd/m ²	IF=120mA
Forward Voltage	VF	—	4.2	4.8	V	IF=120mA
Peak wave length	λP	—	570	—	nm	IF=120mA
Spectral halfwidth	$\Delta \lambda$	—	30	—	nm	IF=120mA
Reverse current	IR	—	—	0.25	mA	VR=8V
Luminous Tolerance	ΔEH	—	—	30	%	IF=120mA

Absolute Maximun Rating(Ta=25°C)

CHARACTERISTICS	SYMBOL	RATING	UNIT
Peak Forward Current	IDD	240	mA
Power Dissipation	Po	1	W
Reverse Voltage	VR	8	V
Operating Temperature	Topr	-20 TO +75	°C
Storage Temperature	Tstg	-30 TO +85	°C

文件編號 : QW0905-L-02401G-B 版本 : B 生效日期 : Sep. 25. 2000