



All dimensions are in mm; tolerances according to ISO 2768 m-H

Description

Rubber sleeves enable the reuse of cable clamps for thinner cables, e.g. fiber optic or power cables in FTTA applications.

Material

Sleeve Silicon, black

Mechanical data

Part	L1 / mm	L2 / mm	D1 / mm	D2 / mm	A / mm	B / mm	Weight in g
SLRS01-C05-0407	52	56	28	32	7	4	43
SLRS01-C05-0711	52	56	28	32	11	7	40
SLRS01-C05-1117	52	56	28	32	17	11	38
SLRS01-C06-0407	55	59	40	44	7	4	105
SLRS01-C06-0711	55	59	40	44	11	7	102
SLRS01-C06-1117	55	59	40	44	17	11	94
SLRS01-C06-1720	55	59	40	44	20	17	84
SLRS01-C06-3032	55	59	40	44	32	30	43

Environmental data

Temperature range -55°C to +75°C
RoHS compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
H. Schütt	04.02.10	E. Truc-Vallet	18.08.14	c00	14-0004	S. Krautenb.	18.08.14