
## KEMET Part Number: M3253506E1Z473JZMB-T&R

(C1210K473J3EML7189)



SMD MIL COG PRF32535, Ceramic, Military/High Reliability, 0.047 uF, 5%, 25 V, COG, SMD, Low ESR, MIL-PRF-32535, N/A, 1210



Dimensions		
L (Imperial)	0.126 Inches +/-0.010 Inches	
L	3.2mm +/-0.25mm	
W (Imperial)	0.098 Inches +/-0.010 Inches	
W	2.49mm +/-0.25mm	
T (Imperial)	0.110 Inches MAX	
Т	2.79mm MAX	
B (Imperial)	0.020 Inches +/-0.014 Inches	
В	0.51mm +/-0.36mm	

Packaging Specifications		
Packaging:	T&R	
Packaging Quantity:	4000	

General Information	
Supplier:	KEMET
Series:	SMD MIL COG PRF32535
Style:	SMD Chip
Description:	SMD, Low ESR, MIL-PRF-32535
RoHS:	No
Termination:	Solder Plated
Failure Rate:	N/A
Qualifications:	MIL-PRF-32535 M-Level
Chip Size:	1210
Shelf Life:	78 Weeks
MSL:	1

Specifications		
Capacitance:	0.047 uF	
Capacitance Tolerance:	5%	
Voltage DC:	25 VDC	
Dielectric Withstanding Voltage:	62.5 V	
Temperature Range:	-55/+125C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.25% 1MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	21.28 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2018 IntelliData.net