



| Part number | L   | B  | Cable           | Wrench | Weight [g] | Picture |
|-------------|-----|----|-----------------|--------|------------|---------|
| SLCC112-C03 | 64  | 25 | 1/2" flexibel   | 10     | 95         |         |
| SLCC112-C05 | 74  | 38 | 7/8" flexibel   | 10     | 140        |         |
| SLCC112-C06 | 85  | 50 | 1 1/4" flexibel | 13     | 180        |         |
| SLCC112-C07 | 99  | 62 | 1 5/8" flexibel | 13     | 240        |         |
| SLCC122-C03 | 91  | 25 | 1/2" flexibel   | 10     | 130        |         |
| SLCC122-C05 | 113 | 38 | 7/8" flexibel   | 10     | 200        |         |
| LCC122-C06  | 138 | 50 | 1 1/4" flexibel | 13     | 270        |         |
| SLCC122-C07 | 164 | 62 | 1 5/8" flexibel | 13     | 370        |         |
| SLCC132-C03 | 117 | 25 | 1/2" flexibel   | 10     | 170        |         |
| SLCC132-C05 | 153 | 38 | 7/8" flexibel   | 10     | 270        |         |
| SLCC132-C06 | 189 | 50 | 1 1/4" flexibel | 13     | 400        |         |
| SLCC132-C07 | 229 | 62 | 1 5/8" flexibel | 13     | 480        |         |

All dimensions are in mm, tolerances acc. To ISO 2768 c-H

**Description**

To install multiple cable runs on towers where space is limited. Without additional adapters, these clamps can provide sturdy, reliable, long-term support to systems by means of tough and UV resistant material.

**Parts list**

| Number | Piece parts         | Material               |
|--------|---------------------|------------------------|
| 1      | Hexagon bolt M6x40  | Stainless steel SUS304 |
| 2      | Nut M6/M8           | Stainless steel SUS304 |
| 3      | Tooth-type washer   | Stainless steel SUS304 |
| 4      | Hooking             | Stainless steel SUS304 |
| 5      | Locking plate       | Stainless steel SUS304 |
| 6      | Plastic cable clamp | Nylon                  |

RF\_35/06.07/5.0

Cable Clamp

SLCC1X2-C0X

**Environmental data**

Temperature -40°C to +70°C  
 Salt spray test 96 hr. acc. to MIL-STD-1344:1977 Method 1001.1  
 UV resistance 300 hr. acc. to ISO 4892-2:2006(E) Method A  
 RoHS compliant

**Tooling**

Hex Wrench 10 / 13mm

**Packaging**

Standard 10 pcs in bag



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date       | Approved     | Date     | Rev. | Engineering change number | Name | Date     |
|-------|------------|--------------|----------|------|---------------------------|------|----------|
| Robin | 08/09/2010 | J. Gramsamer | 03/01/16 | b00  | 16-0005                   | SL   | 02/01/16 |