

# TIP105 TIP106 TIP107

## PNP Plastic Medium-Power Silicon Transistors

### Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- High DC Current Gain :  $h_{FE}=2500$  (Typ) @  $I_C=4.0A$ dc
- Low Collector-Emitter Saturation Voltage
- Monolithic Construction with Built-in Base-Emitter Shunt Resistors
- TO-220 Compact package
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Mounting Torque: 5 in-lbs Maximum
- Halogen free available upon request by adding suffix "-HF"

### Maximum Ratings

Symbol	Rating	Rating	Unit
$V_{CEO}$	Collector-Emitter Voltage	TIP105	60
		TIP106	80
		TIP107	100
$V_{CBO}$	Collector-Base Voltage	TIP105	60
		TIP106	80
		TIP107	100
$V_{EBO}$	Emitter-Base Voltage	5.0	V
$I_C$	Collector Current-continuous	8.0	A
$I_{CP}$	Collector Current-peak	15	A
$I_B$	Base Current	1.0	A
$P_D$	Collector Dissipation @ $T_C=25^\circ C$ Derate above $25^\circ C$	80	W
		0.64	W/ $^\circ C$
$T_J$	Junction Temperature	-55 to +150	$^\circ C$
$T_{STG}$	Storage Temperature	-55 to +150	$^\circ C$

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
--------	-----------	-----	-----	-------

#### OFF CHARACTERISTICS

$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage ( $I_C=30mA$ dc, $I_B=0$ )	TIP105	60	---	Vdc
		TIP106	80	---	
		TIP107	100	---	
$I_{CEO}$	Collector Cut-off Current ( $V_{CE}=30V$ dc, $I_B=0$ ) ( $V_{CE}=40V$ dc, $I_B=0$ ) ( $V_{CE}=50V$ dc, $I_B=0$ )	TIP105	---	50	uAdc
		TIP106	---	50	
		TIP107	---	50	
$I_{CBO}$	Collector Cut-off Current ( $V_{CB}=60V$ dc, $I_E=0$ ) ( $V_{CB}=80V$ dc, $I_E=0$ ) ( $V_{CB}=100V$ dc, $I_E=0$ )	TIP105	---	50	uAdc
		TIP106	---	50	
		TIP107	---	50	
$I_{EBO}$	Emitter Cut-off Current ( $V_{BE}=5.0V$ dc, $I_C=0$ )	---	8.0	mAdc	


#### ON CHARACTERISTICS (1)

$h_{FE(1)}$	DC Current Gain ( $I_C=3.0A$ dc, $V_{CE}=4.0V$ dc) ( $I_C=8.0A$ dc, $V_{CE}=4.0V$ dc)	1000	20000	---
		200	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ( $I_C=3.0A$ dc, $I_B=6.0mA$ dc) ( $I_C=8.0A$ dc, $I_B=80mA$ dc)	---	2.0	Vdc
		---	2.5	
$V_{BE(ON)}$	Base-Emitter On Voltage ( $I_C=8.0A$ dc, $V_{CE}=4.0A$ dc)	---	2.8	Vdc
$h_{fe}$	Small-Signal Current Gain ( $I_C=3.0A$ dc, $V_{CE}=4.0V$ dc, $f=1.0MHz$ )	4.0	---	---
$C_{ob}$	Output Capacitance ( $V_{CB}=10V$ , $I_E=0$ , $f=0.1MHz$ )	---	300	pF

(1) Pulse Test: Pulse Width<300us, Duty Cycle<2%

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

### TO-220



DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	∅
G	.190	.110	2.29	2.79	
H	---	.250	---	6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
T	.230	.270	5.84	6.86	
U	---	.050	---	1.27	
V	.045	---	1.15	---	




Figure 1. Power Derating




Figure 2. Switching Times




Figure 3. Thermal Response




Figure 4. Active-Region Safe Operating Area




Figure 5. Small-Signal Current Gain




Figure 6. Capacitance




Figure 7. DC Current Gain




Figure 8. Collector Saturation Region




Figure 9. "On" Voltages



Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.