

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

FEATURES

- 16 to 50 volt input
- Up to 87% efficiency, 42 W/in³
- Available to Class H, MIL-PRF-38534
- Undervoltage lockout
- -55°C to +125°C operation
- Fully isolated
- Magnetic feedback
- Fixed frequency, 500 kHz typical
- 65 volts for up to 1 sec. transient protection
- Inhibit and sync function
- Output short circuit protection



MODELS	
OUTPUT VOLTAGE (V)	
SINGLE	DUAL
1.8	±5
2.5	±7
3.3	±12
5	±15
5.2	
5.7	
12	
15	
28	

DESCRIPTION

The Interpoint® MFK Series™ of high frequency dc-dc converters offers a wide input voltage range of 16 to 50 volts and up to 25 watts of output power. The converters are capable of withstanding transients of up to 65 volts for up to one second. The package is a hermetically sealed, welded metal case. Flanged and non-flanged models are available.

CONVERTER DESIGN

The MFK converters are switching regulators that use a quasi-square wave, single-ended forward converter design with a constant switching frequency of 500 kHz, typical. Isolation between input and output circuits is provided with transformers in the forward path and in the feedback control loop.

HIGHER POWER DENSITY

The MFK Series offers a new standard of performance for small size and high power density. At just 0.360 inch high and a total footprint of 1.7 in², this low profile package offers a total power density of up to 42 watts per cubic inch.

LOW NOISE, HIGH AUDIO REJECTION

The MFK converters current mode control system provides excellent dynamic response and noise rejection. Audio rejection is typically 50 dB. Output voltage response for a 50% to 100% step load transient is as low as 4% with a 400 μs recovery time.

The MFK Series converters are provided with internal filtering capacitors that help reduce the need for external components in normal operation. Use our FMCE-0328 EMI filter to meet the requirements of MIL-STD-461C CE03 and CS01 and/or MIL-STD-461D, E and F CE102 and CS101 levels of conducted emissions.

INHIBIT FUNCTION

MFK converters provide an inhibit terminal that can be used to disable internal switching, resulting in no output and very low quiescent input current. The converter is inhibited when the inhibit pin is pulled below 0.8 volts. The converter is enabled when the pin, which is internally connected to a pull-up current source, is left unconnected or is connected to an open-collector gate. The open circuit voltage associated with the inhibit pin is 8.5 to 12 V. In the inhibit mode, a maximum of 4 mA must be sunk from the inhibit pin. See Table 5 on page 5 for more information.

SYNCHRONIZATION

A synchronization feature is included with the MFK Series that allows the user to match the switching frequency of the converter to the frequency of a system clock. Synchronization allows the user to adjust the nominal 500 kHz operating frequency to any frequency within the range of 450 kHz to 550 kHz. This is initiated by applying an active high input of the desired frequency to the sync pin. See Table 5 on page 5 for more information.

SHORT CIRCUIT PROTECTION

MFK Series converters provide short circuit protection by restricting the output current to approximately 115% of the full load output current.

UNDERVOLTAGE LOCKOUT

Undervoltage lockout with hysteresis prevents the converters from operating below approximately 15 volts input voltage to keep system current levels smooth, especially during initialization or re-start operations.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT




FIGURE 1: MFK SINGLE BLOCK DIAGRAM




FIGURE 2: MFK DUAL BLOCK DIAGRAM

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

PIN OUT			
Pin	Single Output	MFK2828S	Dual Output
1	Inhibit	Inhibit	Inhibit
2	Output Common	Positive Output	Positive Output
3	Positive Output	No Connection	Output Common
4	Sync In	Output Common	Negative Output
5	Case Ground	Sync In	Sync In
6	Input Common	Case Ground	Case Ground
7	Positive Input	Input Common	Input Common
8	—	Positive Input	Positive Input

TABLE 1: PIN OUT


PINS NOT IN USE	
Inhibit	Leave unconnected
Sync	Leave unconnected

TABLE 2: PINS NOT IN USE



See Figure 32 on page 18 and Figure 34 on page 20 for dimensions.

FIGURE 3: MFK SINGLE PIN OUT (EXCEPT 28S)



See Figure 33 on page 19 and Figure 35 on page 21 for dimensions.

FIGURE 4: MFK DUAL PIN OUT (INCLUDES 28S)

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT




FIGURE 5: MODEL NUMBERING KEY

SMD NUMBERS	
STANDARD MICROCIRCUIT DRAWING (SMD)	MFK SIMILAR PART
5962-1421001HXC	MFK281R8S/883
5962-1421002HXC	MFK282R5S/883
5962-1421003HXC	MFK283R3S/883
5962-1421004HXC	MFK2805S/883
5962-1421009HXC IN PROCESS	MFK285R2S/883
5962-1421005HXC	MFK285R7S/883
5962-1421006HXC	MFK2812S/883
5962-1421007HXC	MFK2815S/883
5962-1421008HTC	MFK2828S/883
5962-1421101HXC	MFK2805D/883
5962-1421102HXC	MFK2807D/883
5962-1421103HXC	MFK2812D/883
5962-1421104HXC	MFK2815D/883

The SMD number shown is for Class H screening, non-flanged. To indicate the flanged case option change the "X" to "Z" in the SMD number ("T" to "U" for 28 single). For exact specifications for an SMD product, refer to the SMD drawing. SMDs can be downloaded from: <http://www.landandmaritime.dla.mil/programs/smcr>

TABLE 3: SMD CROSS REFERENCE

MODEL NUMBER OPTIONS					
TO DETERMINE THE MODEL NUMBER ENTER ONE OPTION FROM EACH CATEGORY IN THE FORM BELOW.					
CATEGORY	Base Model and Input Voltage	Output Voltage ¹	Number of Outputs ²	Case Options ³	Screening ⁴
OPTIONS	MFK28	1R8, 2R5, 3R3, 05 5R2, 5R7, 12, 15, 28	S	(non-flanged, leave blank)	(standard, leave blank)
		05, 07, 12, 15	D	F (flanged)	ES 883
FILL IN FOR MODEL #	MFK28	_____	_____	_____	/ _____

Notes

- Output Voltage: An R indicates a decimal point. 1R8 is 1.8 volts out. The values of 1.8, 2.5, 3.3 and 5.7 volts are only available in single output models.
- Number of Outputs: S is a single output and D is a dual output.
- Case Options: For the standard case, Figure 32 on page 18 or Figure 33 on page 19, leave the case option blank. For the flanged case option, Figure 34 on page 20 or Figure 35 on page 21, insert the letter F in the Case Option position.
- Screening: For standard screening leave the screening option blank. For other screening options, insert the desired screening level. For more information see Table 11 on page 22 and Table 12 on page 23.

TABLE 4: MODEL NUMBER OPTIONS

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 5: OPERATING CONDITIONS, ALL MODELS, 25°C CASE, 28 VIN, 100% LOAD, UNLESS OTHERWISE SPECIFIED.

MFK SERIES		ALL MODELS			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	
LEAD SOLDERING TEMPERATURE ¹	10 SECONDS MAX.	–	–	300	°C
STORAGE TEMPERATURE ¹		-65	–	+150	°C
CASE OPERATING TEMPERATURE	FULL POWER	-55	–	+125	°C
	ABSOLUTE ¹	-55	–	+135	
DERATING OUTPUT POWER/CURRENT ¹	LINEARLY	From 100% at 125°C to 0% at 135°C			
ESD RATING ¹ MIL-PRF-38534, 3.9.5.8.2	MIL-STD-883, METHOD 3015 CLASS 2	2000 - 3999 ²			V
ISOLATION: INPUT TO OUTPUT OR ANY PIN TO CASE EXCEPT CASE PIN	500 VDC AT 25°C	100	–	–	Megohms
UNDERVOLTAGE LOCKOUT		–	15	–	V
CURRENT LIMIT ³	% OF FULL LOAD	–	115	–	%
AUDIO REJECTION ¹		–	50	–	dB
CONVERSION FREQUENCY	FREE RUN -55°C TO +125°C	430	–	570	kHz
SYNCHRONIZATION	INPUT FREQUENCY	450	–	550	kHz
	DUTY CYCLE ¹	40	–	60	%
	ACTIVE LOW	–	–	0.8	V
	ACTIVE HIGH ¹	4.5	–	5.0	
	REFERENCED TO		INPUT COMMON		
	IF NOT USED		LEAVE UNCONNECTED		
INHIBIT ACTIVE LOW (OUTPUT DISABLED) Do not apply a voltage to the inhibit pin ⁵	INHIBIT PIN PULLED LOW ⁴	–	–	0.8	V
	INHIBIT PIN SOURCE CURRENT ¹	–	–	4	mA
	REFERENCED TO		INPUT COMMON		
INHIBIT ACTIVE HIGH (OUTPUT ENABLED) Do not apply a voltage to the inhibit pin ⁵	INHIBIT PIN CONDITION	OPEN COLLECTOR OR UNCONNECTED			
	OPEN PIN VOLTAGE ¹	8.5	–	12	V

*For mean time between failures (MTBF) contact Applications Engineering
powerapps@crane-eg.com +1 425-882-3100 option 7*

Notes

1. Guaranteed by characterization test and/or analysis. Not a production test.
2. Passes 2000 volts.
3. Dual outputs: The over-current limit will trigger when the sum of the currents from both outputs reaches 115% (typical value) of the maximum rated "total" current of both outputs.

4. Tested with inhibit pin pulled to ground.

5. An external inhibit interface should be used to pull the inhibit low or leave it floating. The inhibit pin can be left unconnected if not used.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 6: ELECTRICAL CHARACTERISTICS -55°C TO +125°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.

SINGLE OUTPUT MODELS		MFK281R8S			MFK282R5S			MFK283R3S			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE		1.74	1.80	1.86	2.42	2.50	2.58	3.20	3.30	3.40	V
OUTPUT CURRENT ²	V _{IN} = 16 TO 50	—	—	5.56	—	—	5.0	—	—	4.55	A
OUTPUT POWER ²	V _{IN} = 16 TO 50	—	—	10	—	—	12.5	—	—	15	W
OUTPUT RIPPLE	T _C = 25°C	—	30	60	—	30	60	—	25	60	mV p-p
10 kHz - 20 MHz	T _C = -55°C TO +125°C	—	35	80	—	35	80	—	30	80	
LINE REGULATION	V _{IN} = 16 TO 50	—	5	20	—	5	20	—	5	20	mV
LOAD REGULATION	NO LOAD TO FULL	—	10	25	—	5	25	—	5	25	mV
INPUT VOLTAGE	CONTINUOUS	16	28	50	16	28	50	16	28	50	V
NO LOAD TO FULL	TRANSIENT 1 sec. ¹	—	—	65	—	—	65	—	—	65	V
INPUT CURRENT	NO LOAD	—	25	50	—	25	50	—	25	50	mA
	INHIBITED	—	2.5	4	—	2.5	4	—	2.5	4	
INPUT RIPPLE CURRENT	10 kHz - 20 MHz	—	30	75	—	30	80	—	30	80	mA p-p
EFFICIENCY	TC = 25°C	69	72	—	73	76	—	76	79	—	%
	TC = -55°C TO +125°C	67	—	—	71	—	—	74	—	—	
LOAD FAULT ^{3, 4}	POWER DISSIPATION	—	—	8.5	—	—	8.5	—	—	8.5	W
SHORT CIRCUIT	RECOVERY ¹	—	—	20	—	—	20	—	—	20	ms
STEP LOAD RESPONSE ^{5, 6}	TRANSIENT	—	125	200	—	125	200	—	125	200	mV pk
50% - 100% - 50%	RECOVERY	—	200	400	—	100	300	—	200	300	
STEP LINE RESPONSE ^{1, 5, 7}	TRANSIENT	—	—	350	—	—	350	—	—	350	mV pk
16 - 50 - 16 V	RECOVERY	—	0.5	1	—	0.5	1	—	0.5	1	
START-UP ⁸	DELAY	—	—	25	—	—	25	—	—	25	ms
FULL LOAD	OVERSHOOT ¹	—	—	50	—	—	50	—	—	50	mV pk
CAPACITIVE LOAD ¹	NO EFFECT ON DC	—	—	2000	—	—	2000	—	—	2000	μF
T _C = 25°C	PERFORMANCE										

Notes

1. Guaranteed by characterization test and/or analysis. Not a production test.
2. A minimum load of 20% is recommended.
3. Short circuit measured with 1% 10 milliohm resistive load.
4. Indefinite short circuit protection not guaranteed above 125°C.

5. Recovery and startup times are measured from application of the transient or change in condition to the point at which V_{OUT} is within 1% of final value. C_L = 0.
6. Step load transition time 10 μs ± 1 μs.
7. Step line transition time 100 μs ± 20 μs.
8. Tested on release from inhibit.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 7: ELECTRICAL CHARACTERISTICS -55°C TO +125°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.

SINGLE OUTPUT MODELS		MFK2805S			MFK285R2S			MFK285R7S			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE		4.85	5.00	5.15	5.05	5.2	5.35	5.52	5.70	5.87	V
OUTPUT CURRENT ²	V _{IN} = 16 TO 50	—	—	4.0	—	—	4	—	—	4.0	A
OUTPUT POWER ²	V _{IN} = 16 TO 50	—	—	20	—	—	20.8	—	—	22.8	W
OUTPUT RIPPLE	T _C = 25°C	—	40	80	—	40	80	—	40	80	mV p-p
10 kHz - 20 MHz	T _C = -55°C TO +125°C	—	—	100	—	—	100	—	—	100	
LINE REGULATION	V _{IN} = 16 TO 50	—	5	20	—	5	20	—	5	20	mV
LOAD REGULATION	NO LOAD TO FULL	—	5	25	—	5	25	—	5	25	mV
INPUT VOLTAGE	CONTINUOUS	16	28	50	16	28	50	16	28	50	V
NO LOAD TO FULL	TRANSIENT 1 sec. ¹	—	—	65	—	—	65	—	—	65	V
INPUT CURRENT	NO LOAD	—	25	50	—	25	50	—	25	50	mA
	INHIBITED	—	2.4	4	—	2.4	4	—	2.4	4	
INPUT RIPPLE CURRENT	10 kHz - 20 MHz	—	40	85	—	40	85	—	40	85	mA p-p
EFFICIENCY	T _C = 25°C	79	82	—	79	82	—	79	82	—	%
	T _C = -55°C TO +125°C	77	—	—	77	—	—	77	—	—	
LOAD FAULT ^{3, 4}	POWER DISSIPATION	—	6	8.5	—	6	8.5	—	6	8.5	W
SHORT CIRCUIT	RECOVERY ¹	—	—	20	—	—	20	—	—	20	ms
STEP LOAD RESPONSE ^{5, 6}	TRANSIENT	—	—	400	—	—	400	—	—	400	mV pk
50% - 100% - 50%	RECOVERY	—	—	300	—	—	300	—	—	300	
STEP LINE RESPONSE ^{1, 5, 7}	TRANSIENT	—	—	500	—	—	500	—	—	570	mV pk
16 - 50 - 16 V	RECOVERY	—	0.5	1	—	0.5	1	—	0.5	1	
START-UP ⁸	DELAY	—	—	25	—	—	25	—	—	25	ms
FULL LOAD	OVERSHOOT ¹	—	0	50	—	0	50	—	0	50	mV pk
CAPACITIVE LOAD ¹	NO EFFECT ON DC	—	—	2000	—	—	2000	—	—	2000	μF
T _C = 25°C	PERFORMANCE	—	—	2000	—	—	2000	—	—	2000	

Notes

1. Guaranteed by characterization test and/or analysis. Not a production test.
2. A minimum load of 20% is recommended.
3. Short circuit measured with 1% 10 milliohm resistive load.
4. Indefinite short circuit protection not guaranteed above 125°C.

5. Recovery and startup times are measured from application of the transient or change in condition to the point at which V_{OUT} is within 1% of final value. C_L = 0.
6. Step load transition time 10 μs ± 1 μs.
7. Step line transition time 100 μs ± 20 μs.
8. Tested on release from inhibit.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 8: ELECTRICAL CHARACTERISTICS -55°C TO +125°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.

SINGLE OUTPUT MODELS		MFK2812S			MFK2815S			MFK2828S			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE		11.76	12.00	12.24	14.70	15.00	15.30	27.16	28.00	28.84	V
OUTPUT CURRENT ²	V _{IN} = 16 TO 50	—	—	2.08	—	—	1.67	—	—	0.89	A
OUTPUT POWER ²	V _{IN} = 16 TO 50	—	—	25	—	—	25	—	—	25	W
OUTPUT RIPPLE 10 kHz - 20 MHz	T _C = 25°C	—	35	80	—	40	80	—	80	150	mV p-p
	T _C = -55°C TO +125°C	—	—	100	—	50	100	—	100	200	
LINE REGULATION	V _{IN} = 16 TO 50	—	5	20	—	5	20	—	150	280	mV
LOAD REGULATION	NO LOAD TO FULL	—	5	20	—	5	20	—	150	280	mV
INPUT VOLTAGE	CONTINUOUS	16	28	50	16	28	50	16	28	50	V
NO LOAD TO FULL	TRANSIENT 1 sec. ¹	—	—	65	—	—	65	—	—	65	V
INPUT CURRENT	NO LOAD	—	20	50	—	20	50	—	30	55	mA
	INHIBITED	—	2.5	4	—	2.5	4	—	2.5	4	
INPUT RIPPLE CURRENT	10 kHz - 20 MHz	—	45	90	—	50	110	—	50	100	mA p-p
EFFICIENCY	T _C = 25°C	83	86	—	84	87	—	81	84	—	%
	T _C = -55°C TO +125°C	81	—	—	82	—	—	80	—	—	
LOAD FAULT ^{3, 4}	POWER DISSIPATION	—	6	8.5	—	6	8	—	6	8.5	W
SHORT CIRCUIT	RECOVERY ¹	—	—	20	—	—	20	—	—	20	ms
STEP LOAD RESPONSE ^{5, 6} 50% - 100% - 50%	TRANSIENT	—	350	500	—	400	600	—	900	1200	mV pk
	RECOVERY	—	300	500	—	300	500	—	500	600	μs
STEP LINE RESPONSE ^{1, 5, 7} 16 - 50 - 16 V	TRANSIENT	—	—	1300	—	—	1500	—	—	2800	mV pk
	RECOVERY	—	0.5	1	—	0.5	1	—	0.5	1	ms
START-UP ⁸	DELAY	—	—	25	—	—	25	—	—	25	ms
FULL LOAD	OVERSHOOT ¹	—	0	120	—	0	150	—	0	280	mV pk
CAPACITIVE LOAD ¹ T _C = 25°C	NO EFFECT ON DC PERFORMANCE	—	—	2000	—	—	2000	—	—	1000	μF

Notes

- Guaranteed by characterization test and/or analysis. Not a production test.
- A minimum load of 20% is recommended.
- Short circuit measured with 1% 10 milliohm resistive load.
- Indefinite short circuit protection not guaranteed above 125°C.

- Recovery and startup times are measured from application of the transient or change in condition to the point at which V_{OUT} is within 1% of final value. C_L = 0.
- Step load transition time 10 μs ± 1 μs
- Step line transition time 100 μs ± 20 μs.
- Tested on release from inhibit.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 9: ELECTRICAL CHARACTERISTICS -55°C TO +125°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.

DUAL OUTPUT MODELS		MFK2805D			MFK2807D			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE	+ V _{OUT}	4.85	5.00	5.15	6.86	7.00	7.14	V
	- V _{OUT}	4.82	5.00	5.18	6.83	7.00	7.17	
OUTPUT CURRENT ^{2, 3} V _{IN} = 16 TO 50 V	EITHER OUTPUT	—	±2.0	2.80	—	±1.5	2.10	A
	TOTAL OUTPUT	—	—	4.0	—	—	3.0	
OUTPUT POWER ^{2, 3} V _{IN} = 16 TO 50 V	EITHER OUTPUT	—	±10	18	—	±10.5	18.9	W
	TOTAL OUTPUT	—	—	20	—	—	21	
OUTPUT RIPPLE ±V _{OUT} , 10 kHz - 20 MHz	T _C = 25°C	—	—	80	—	—	70	mV p-p
	T _C = -55°C TO +125°C	—	—	90	—	—	80	
LINE REGULATION V _{IN} = 16 TO 50 V	+ V _{OUT}	—	5	20	—	5	20	mV
	- V _{OUT}	—	20	100	—	20	100	
LOAD REGULATION NL TO FULL, BALANCED	+ V _{OUT}	—	5	20	—	5	20	mV
	- V _{OUT}	—	35	250	—	50	250	
CROSS REGULATION ⁴	T _C = 25°C	—	—	360	—	—	400	mV
INPUT VOLTAGE	CONTINUOUS	16	28	50	16	28	50	V
	TRANSIENT 1 sec. ¹	—	—	65	—	—	65	V
INPUT CURRENT	NO LOAD	—	30	50	—	30	50	mA
	INHIBITED	—	2.5	4	—	2.5	4	
INPUT RIPPLE CURRENT	10 kHz - 20 MHz	—	35	70	—	35	70	mA p-p
EFFICIENCY	T _C = 25°C	78	81	—	81	83	—	%
	T _C = -55°C TO +125°C	76	—	—	79	—	—	
LOAD FAULT ^{5, 6}	POWER DISSIPATION	—	6	8.5	—	6	8	W
SHORT CIRCUIT	RECOVERY ¹	—	15	20	—	15	20	ms
STEP LOAD RESPONSE ^{7, 8, 9} 50%-100%-50%, BALANCED LOADS	TRANSIENT ±V _{OUT}	—	100	450	—	125	500	mV pk
	RECOVERY	—	200	500	—	200	500	μs
STEP LINE RESPONSE ^{1, 7, 10} ±V _{OUT} , V _{IN} = 16 - 50 - 16 V	TRANSIENT	—	—	500	—	—	700	mV pk
	RECOVERY	—	0.5	1	—	0.5	1	ms
START-UP ¹¹	DELAY	—	—	20	—	—	20	ms
	OVERSHOOT ¹	—	0	50	—	0	70	mV pk
CAPACITIVE LOAD ^{1, 12} T _C = 25°C	NO EFFECT ON DC	—	—	1000	—	—	1000	μF
	PERFORMANCE	—	—	1000	—	—	1000	

Notes

- Guaranteed by characterization test and/or analysis. Not a production test.
- Up to 70% of the total output power is available from either output providing the opposite output is simultaneously carrying 30% of the total output power.
- Recommended minimum load is 20% total load (sum of both outputs).
- Effect on -V_{out} for the following conditions:
+P_o = 30% to 70%; - P_o = 70% to 30%
- Short circuit measured with 1% 10 milliohm resistive load.
- Indefinite short circuit protection not guaranteed above 125°C (case)

- Recovery and startup times are measured from application of the transient or change in condition to the point at which V_{OUT} is within 1% of final value. C_L = 0.
- Response of either output with the opposite output held at half of the total output power.
- Step load transition time 10 μs ±1 μs.
- Step line transition time >100 μs.
- Tested on release from inhibit.
- Each output.

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TABLE 10: ELECTRICAL CHARACTERISTICS -55°C TO +125°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.

DUAL OUTPUT MODELS		MFK2812D			MFK2815D			UNITS
PARAMETER	CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT VOLTAGE	+ V _{OUT}	11.76	12.00	12.24	14.70	15.00	15.30	V
	- V _{OUT}	11.70	12.00	12.30	14.63	15.00	15.38	
OUTPUT CURRENT ^{2, 3} V _{IN} = 16 TO 50 V	EITHER OUTPUT	—	±1.04	1.45	—	±0.833	1.16	A
	TOTAL OUTPUT	—	—	2.08	—	—	1.66	
OUTPUT POWER ^{2, 3} V _{IN} = 16 TO 50 V	EITHER OUTPUT	—	±12.5	22.5	—	±12.5	22.5	W
	TOTAL OUTPUT	—	—	25	—	—	25	
OUTPUT RIPPLE ±V _{OUT} , 10 kHz - 20 MHz	T _C = 25°C	—	—	90	—	—	90	mV p-p
	T _C = -55°C TO +125°C	—	—	90	—	—	90	
LINE REGULATION V _{IN} = 16 TO 50 V	+ V _{OUT}	—	5	20	—	5	20	mV
	- V _{OUT}	—	20	150	—	20	150	
LOAD REGULATION NL TO FULL, BALANCED	+ V _{OUT}	—	5	20	—	5	20	mV
	- V _{OUT}	—	60	250	—	100	250	
CROSS REGULATION ⁴	T _C = 25°C	—	—	700	—	—	800	mV
INPUT VOLTAGE	CONTINUOUS	16	28	50	16	28	50	V
	TRANSIENT 1 sec. ¹	—	—	65	—	—	65	V
INPUT CURRENT	NO LOAD	—	30	50	—	30	50	mA
	INHIBITED	—	2.5	4	—	2.5	4	
INPUT RIPPLE CURRENT	10 kHz - 20 MHz	—	50	100	—	40	100	mA p-p
EFFICIENCY	T _C = 25°C	82	85	—	83	86	—	%
	T _C = -55°C TO +125°C	80	—	—	81	—	—	
LOAD FAULT ^{5, 6}	POWER DISSIPATION	—	5	8	—	5	8	W
SHORT CIRCUIT	RECOVERY ¹	—	15	20	—	15	20	ms
STEP LOAD RESPONSE ^{7, 8, 9} 50%-100%-50%, BALANCED LOADS	TRANSIENT ±V _{OUT}	—	350	600	—	400	650	mV pk
	RECOVERY	—	250	550	—	250	550	μs
STEP LINE RESPONSE ^{1, 7, 10} ±V _{OUT} , V _{IN} = 16 - 50 - 16 V	TRANSIENT	—	—	1300	—	—	1500	mV pk
	RECOVERY	—	0.5	1	—	0.5	1	ms
START-UP ¹¹	DELAY	—	—	20	—	—	20	ms
	OVERSHOOT ¹	—	0	120	—	0	150	mV pk
CAPACITIVE LOAD ^{1, 12} T _C = 25°C	NO EFFECT ON DC	—	—	1000	—	—	1000	μF
	PERFORMANCE	—	—	1000	—	—	1000	

Notes


- Guaranteed by characterization test and/or analysis. Not a production test.
- Up to 70% of the total output power is available from either output providing the opposite output is simultaneously carrying 30% of the total output power.
- Recommended minimum load is 20% total load (sum of both outputs).
- Effect on -V_{out} for the following conditions:
+P_o = 30% to 70%; - P_o = 70% to 30%
- Short circuit measured with 1% 10 milliohm resistive load.
- Indefinite short circuit protection not guaranteed above 125°C (case)

- Recovery and startup times are measured from application of the transient or change in condition to the point at which V_{OUT} is within 1% of final value. C_L = 0.
- Response of either output with the opposite output held at half of the total output power.
- Step load transition time 10 μs ±1 μs.
- Step line transition time >100 μs.
- Tested on release from inhibit.
- Each output.

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK SINGLE AUDIO REJECTION

FIGURE 6




MFK2805S INPUT RIPPLE

FIGURE 7



MFK2805S OUTPUT RIPPLE

FIGURE 8




MFK2805S STEP LOAD 50% - 100%

FIGURE 9

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK2805S STEP LOAD 100% - 50%

FIGURE 10




MFK2805S STEP LINE 16 - 50 VOLTS 50% LOAD

FIGURE 11



MFK2805S STEP LINE 50 - 16 VOLTS 50% LOAD

FIGURE 12




MFK2805S START-UP FULL LOAD

FIGURE 13

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK281R8S EFFICIENCY

FIGURE 14




MFK282R5S EFFICIENCY

FIGURE 15



MFK283R3S EFFICIENCY

FIGURE 16




MFK2805S EFFICIENCY

FIGURE 17


MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK2812S EFFICIENCY
FIGURE 18



MFK2815S EFFICIENCY
FIGURE 19

MFK285R7S Efficiency will be added in the future.




MFK2828S EFFICIENCY
FIGURE 20

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK DUAL AUDIO REJECTION

FIGURE 21




MFK2815D INPUT RIPPLE

FIGURE 22



MFK2815D OUTPUT RIPPLE

FIGURE 23




MFK2815D STEP LOAD 50% - 100%

FIGURE 24

MFK Single and Dual DC-DC Converters


16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
 FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK2815D STEP LOAD 100% - 50%

FIGURE 25




MFK2815D STEP LINE 16 - 50 VOLTS 50% LOAD

FIGURE 26



MFK2815D STEP LINE 50 - 16 VOLTS 50% LOAD

FIGURE 27




MFK2815D START-UP FULL LOAD

FIGURE 28


MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

TYPICAL PERFORMANCE PLOTS: 25°C CASE, 28 VIN, 100% LOAD, FREE RUN, UNLESS OTHERWISE SPECIFIED.
FOR REFERENCE ONLY, NOT GUARANTEED SPECIFICATIONS.




MFK2805D EFFICIENCY
FIGURE 29



MFK2812D EFFICIENCY
FIGURE 30

MFK2807D Efficiency will be added in the future.




MFK2815D EFFICIENCY
FIGURE 31

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

BOTTOM VIEW MFK SINGLE



Weight: 38 grams maximum

Case dimensions in inches (mm)

Tolerance ± 0.005 (0.13) for three decimal places
 ± 0.01 (0.3) for two decimal places
 unless otherwise specified

CAUTION

Heat from reflow or wave soldering may damage the device. Solder pins individually with heat application not exceeding 300°C for 10 seconds per pin.

Materials

Header Cold Rolled Steel/Nickel/Gold

Cover Kovar/Nickel

Pins #52 alloy/Gold ceramic seal

Gold plating of 50 - 150 microinches included in pin diameter

Seal Hole: 0.123 ± 0.002 (3.12 ± 0.05)

Please refer to the numerical dimensions for accuracy.

Case E5, Rev G, 2015.04.21


FIGURE 32: MFK SINGLE OUTPUT

EXCEPT 28 VOLT SINGLE

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

BOTTOM VIEW MFK DUAL



Weight: 38 grams maximum

Case dimensions in inches (mm)

Tolerance ± 0.005 (0.13) for three decimal places
 ± 0.01 (0.3) for two decimal places
 unless otherwise specified

CAUTION

Heat from reflow or wave soldering may damage the device. Solder pins individually with heat application not exceeding 300°C for 10 seconds per pin.

Materials

Header Cold Rolled Steel/Nickel/Gold

Cover Kovar/Nickel

Pins #52 alloy/Gold ceramic seal

Gold plating of 50 - 150 microinches included in pin diameter

Seal Hole: 0.091 ± 0.002 (2.31 ± 0.05)

Please refer to the numerical dimensions for accuracy.

Case E6, Rev F, 2015.04.21

FIGURE 33: MFK DUAL OUTPUT

INCLUDES 28 VOLT SINGLE

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

ELEMENT EVALUATION ¹ HIGH RELIABILITY /883 (CLASS H)

COMPONENT-LEVEL TEST PERFORMED	QML	
	CLASS H /883	
	M/S ²	P ³
Element Electrical	■	■
Visual	■	■
Internal Visual	■	
Final Electrical	■	■
Wire Bond Evaluation	■	■

- Notes
1. Element evaluation does not apply to standard and /ES product.
 2. M/S = Active components (microcircuit and semiconductor die).
 3. P = Passive components, Class H element evaluation. Not applicable to standard and /ES element evaluation.

TABLE 11: ELEMENT EVALUATION

MFK Single and Dual DC-DC Converters

16 TO 50 VOLTS INPUT – 25 WATT

ENVIRONMENTAL SCREENING HIGH RELIABILITY STANDARD, /ES AND /883 (CLASS H)

TEST PERFORMED	NON-QML ¹		QML ²
	STANDARD	/ES	CLASS H /883
Pre-cap Inspection, Method 2017, 2032	■	■	■
Temperature Cycle (10 times)			
Method 1010, Cond. C, -65°C to +150°C, ambient			■
Method 1010, Cond. B, -55°C to +125°C, ambient		■	
Constant Acceleration			
Method 2001, 3000 g			■
Method 2001, 500 g		■	
PIND, Test Method 2020, Cond. A			■ ³
Burn-in Method 1015, +125°C case, typical ⁴			
96 hours		■	
160 hours			■
Final Electrical Test, MIL-PRF-38534, Group A,			
Subgroups 1 through 6, -55°C, +25°C, +125°C case			■
Subgroups 1 and 4, +25°C case	■	■	
Hermeticity Test			
Gross Leak, Cond. C ₁ , fluorocarbon		■	■
Fine Leak, Cond. A ₂ , helium		■	■
Gross Leak, Dip	■		
Final visual inspection, Method 2009	■	■	■

Test methods are referenced to MIL-STD-883 as determined by MIL-PRF-38534.

Notes

- Standard and ES are non-QML products and may not meet all of the requirements of MIL-PRF-38534.
- All processes are QML qualified and performed by certified operators.
- Not required by DLA but performed to assure product quality.
- Burn-in temperature designed to bring the case temperature to +125°C minimum.
Burn-in is a powered test.

TABLE 12: ENVIRONMENTAL SCREENING