

# PT100 or Thermocouple Input DIN Rail Transmitter



## DS3018

### Features:

- Configuration using USB port powered configurator
- PT100 or Thermocouple / mV
- Isolated input
- Input linear to temperature
- 4-20mA two wire output



### Description:

The GEN1603 series is a cost effective DIN rail mounted temperature transmitter. The range consists of two versions, the GEN1603/P accepts PT100 inputs, and the GEN1603/TC accepts seven common thermocouple types plus mV input.

Designed for ease of use, this range is configured with our USB port powered configuration module. The module interfaces a PC USB port to the GEN1603, using the 4-20mA loop to communicate. You will be able to read the current configuration data, and then perform any changes you wish to make to the configuration. To further save time, the GEN1603 and configuration module do not need to be wired to a power supply during the configuration process, both are powered by the USB interface on your PC.

Model	Input Type	Low Range	High Range	Units	Burnout
GEN1603/P	PT100	Input @ 4mA	Input @ 20mA	°F, °C	Up/Scale Down/Scale



### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Roxspur Measurement & Control  
2 Downgate Drive, Sheffield, South Yorkshire, S4 8BT, UK | Ph: +44 (0) 114-244-2521  
www.ttelectronics.com | RoxspurSales@ttelectronics.com

# PT100 or Thermocouple Input DIN Rail Transmitter



INPUT	RANGE	ACCURACY* <sup>1</sup>	STABILITY* <sup>3</sup>
K	-200 to 1370°C	0.1% of FSR ±0.5°C (type T 0.2% FSR ±0.5°C)	±0.01% of FSR/°C
J	-100 to 1200°C		
E	-100 to 1000°C		
N	-180 to 1300°C		
T	-100 to 400°C		
R	-10 to 1760°C	±0.5°C ±0.1% of FSR* <sup>2</sup>	
S	-10 to 1760°C	±0.5°C ±0.1% of FSR* <sup>2</sup>	
mV	-40 to 75mV	±0.04mV	
P	-200 to 850°C	±0.1°C / ±0.05% of reading	±0.005% of FSR/°C

\*<sup>1</sup> Accuracy for PT100 and thermocouples do not include sensor and cold junction errors.

\*<sup>2</sup> Only over the range 800 to 1600°C.

\*<sup>3</sup> Ambient -10 to 50°C.

**General Note**

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Roxspur Measurement & Control  
2 Downgate Drive, Sheffield, South Yorkshire, S4 8BT, UK | Ph: +44 (0) 114-244-2521  
www.ttelectronics.com | RoxspurSales@ttelectronics.com

# PT100 or Thermocouple Input DIN Rail Transmitter



OUTPUT	
Type	Two wire current sink; signal range 4-20mA; full range 3.8-24mA
Supply	11-30V DC, 24V nominal giving Max loop load of 600R @ 24V
Response Time	<500ms to reach 95% of final value; start-up time <3s
Calibration Accuracy	±5µA
Loop Effects	Loop ripple 0.03% of FSR; supply sensitivity 0.05µA/°C; supply ripple rejection <5µA error @ 1V rms 50Hz ripple
Protection	Reverse connection and over-voltage protection. Max over voltage current 100mA.
Stability	±5µA/°C
GENERAL	
Isolation	Input to output tested at 500V DC
Ambient	Operating -20 to 70°C, 10 to 95% RH non-condensing. Storage -40 to 85°C
Approvals	CE tested to BS EN 61326
MECHANICAL	
Material	Polmide 6.6
Terminals	Screw terminal
Cable	2.5mm max.
Colour	Grey

**General Note**

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Roxspur Measurement & Control  
2 Downgate Drive, Sheffield, South Yorkshire, S4 8BT, UK | Ph: +44 (0) 114-244-2521  
www.ttelectronics.com | RoxspurSales@ttelectronics.com