



CUI INC
Part No: CLS0301-L152
Description: speaker
Date: 7/03/2007
Unit: mm
Page No: 1 of 2

Specifications




Nominal Size	30 mm		
Impedance	8 Ohm ± 15%	at	1 KHz 1 V
Resonant frequency	550 Hz ± 110 Hz	at	1 V
Sound pressure level	86 dB/w ± 3 dB	1 w 50 cm ave. at 0.8K, 1K, 1.2K, 1.5K Hz	
Response	Fo Hz ~ 20 KHz max 10 dB		
Input power	Nominal	1 W	Handling capacity 2 W
Operation	must be normal at program source 1 W		
Buzz, rattle, etc.	must be normal at sine wave 2.83 V		
Magnet	Size: 12.5 x 1.5 mm		
Load test	White noise	1 W	for 24 hours
Heat test	70 ± 2° C	20-50% R.H.	24 hours
Humidity test	40 ± 2° C	90-95% R.H.	24 hours

Frequency Response Curve

Potentiometer range	50 dB
Rectifier	RMS
Lower limit frequency	20 Hz
Wr. speed	100 mm/sec


Zero level 60 dB

REV.	DESCRIPTION	DATE
A	NEW DRAWING	7/3/2007



RoHS

SPECIFICATIONS:
WIRE: UL1007, #28AWG
LENGTH: 152mm

TOLERANCE:
±0.5mm UNLESS OTHERWISE
SPECIFIED



20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-612-2383
Website: www.cui.com

TITLE: LOW PROFILE SPEAKER	REV: A
PART NO: CLS0301-L152	UNITS: MM [INCHES]
DRAWN BY: ZRJ	APPROVED BY:
	SCALE: 2:1