


DATA SHEET



PSS8050

NPN medium power 25 V transistor

Product specification

2002 Nov 18

NPN medium power 25 V transistor

PSS8050

FEATURES

- High total power dissipation
- High current capability.

APPLICATIONS

- Medium power switching and muting
- Amplification
- Portable radio output amplifier (class-B, push-pull).

DESCRIPTION

NPN transistor in a SOT54 (TO-92) plastic package.
PNP complement: PSS8550.

MARKING

TYPE NUMBER	MARKING CODE
PSS8050C	S8050C
PSS8050D	S8050D

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	UNIT
V_{CE0}	collector-emitter voltage	25	V
I_C	collector current (DC)	1.5	A

PINNING

PIN	DESCRIPTION
1	collector
2	base
3	emitter




Fig.1 Simplified outline (SOT54).

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CBO}	collector-base voltage	open emitter	–	40	V
V_{CEO}	collector-emitter voltage	open base	–	25	V
V_{EBO}	emitter-base voltage	open collector	–	6	V
I_C	collector current (DC)		–	1.5	A
I_{CM}	peak collector current		–	2	A
I_B	base current (DC)		–	300	mA
I_{BM}	peak base current		–	1	A
P_{tot}	total power dissipation	$T_{amb} \leq 25\text{ }^\circ\text{C}$; note 1	–	850	mW
		$T_{amb} \leq 25\text{ }^\circ\text{C}$; note 2	–	900	mW
		$T_{amb} \leq 25\text{ }^\circ\text{C}$; note 3	–	1	W
T_{stg}	storage temperature		–65	+150	$^\circ\text{C}$
T_j	junction temperature		–	150	$^\circ\text{C}$
T_{amb}	operating ambient temperature		–65	+150	$^\circ\text{C}$

Notes

1. Device mounted on a printed-circuit board; single sided copper; tinplated; standard footprint.
2. Device mounted on a printed-circuit board; single sided copper; tinplated; mounting pad for collector 1 cm².
3. Device mounted on a printed-circuit board; single sided copper; tinplated; standard footprint. Operated under pulsed conditions: pulse width $t_p \leq 1\text{ s}$; duty cycle $\delta \leq 0.75\%$.

NPN medium power 25 V transistor

PSS8050

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-a}$	thermal resistance from junction to ambient	in free air; note 1	147	K/W
		in free air; note 2	139	K/W
		in free air; note 3	125	K/W

Notes

- Device mounted on a printed-circuit board; single sided copper; tinplated; standard footprint.
- Device mounted on a printed-circuit board; single sided copper; tinplated; mounting pad for collector 1 cm².
- Device mounted on a printed-circuit board; single sided copper; tinplated; standard footprint.
Operated under pulsed conditions: pulse width $t_p \leq 1$ s; duty cycle $\delta \leq 0.75\%$.





CHARACTERISTICS

$T_{amb} = 25$ °C unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{CBO}	collector-base cut-off current	$V_{CB} = 35$ V; $I_E = 0$	–	–	100	nA
		$V_{CB} = 35$ V; $I_E = 0$; $T_{amb} = 150$ °C	–	–	50	μA
I_{CEO}	collector-emitter cut-off current	$V_{CE} = 25$ V; $I_B = 0$	–	–	100	nA
I_{EBO}	emitter-base cut-off current	$V_{EB} = 6$ V; $I_C = 0$	–	–	100	nA
h_{FE}	DC current gain	$I_C = 5$ mA; $V_{CE} = 1$ V	45	–	–	
		$I_C = 800$ mA; $V_{CE} = 1$ V	40	–	–	
	DC current gain PSS8050C PSS8050D	$I_C = 100$ mA; $V_{CE} = 1$ V	120 160	– –	200 300	
V_{CEsat}	collector-emitter saturation voltage	$I_C = 800$ mA; $I_B = 80$ mA	–	165	500	mV
V_{BEsat}	base-emitter saturation voltage	$I_C = 800$ mA; $I_B = 80$ mA	–	–	1.2	V
V_{BEon}	base-emitter turn-on voltage	$I_C = 10$ mA; $V_{CE} = 1$ V	–	–	1	V
f_T	transition frequency	$I_C = 50$ mA; $V_{CE} = 10$ V; $f = 100$ MHz	100	–	–	MHz
C_c	collector capacitance	$V_{CB} = 10$ V; $I_E = I_e = 0$; $f = 1$ MHz	–	–	10	pF



NPN medium power 25 V transistor

PSS8050







NPN medium power 25 V transistor

PSS8050





NPN medium power 25 V transistor

PSS8050



NPN medium power 25 V transistor

PSS8050




NPN medium power 25 V transistor

PSS8050

PACKAGE OUTLINE

Plastic single-ended leaded (through hole) package; 3 leads

SOT54



NPN medium power 25 V transistor

PSS8050

DATA SHEET STATUS

LEVEL	DATA SHEET STATUS ⁽¹⁾	PRODUCT STATUS ⁽²⁾⁽³⁾	DEFINITION
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

Notes

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.
3. For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

DEFINITIONS

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

DISCLAIMERS

Life support applications — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

NPN medium power 25 V transistor

PSS8050

NOTES

NPN medium power 25 V transistor

PSS8050

NOTES

Philips Semiconductors – a worldwide company

Contact information

For additional information please visit <http://www.semiconductors.philips.com>. Fax: +31 40 27 24825

For sales offices addresses send e-mail to: sales.addresses@www.semiconductors.philips.com.

© Koninklijke Philips Electronics N.V. 2002

SCA74

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

613514/01/pp12

Date of release: 2002 Nov 18

Document order number: 9397 750 10625

Let's make things better.

**Philips
Semiconductors**



PHILIPS