


PRODUCT INFORMATION

750nm
850nm

1A354
High-Performance PIN

Datacom, General Purpose

The very high speed and low capacitance of this GaAs PIN Photodiode makes it ideal for datacom and general purpose applications. Its double-lens optical system is designed for single-mode fiber as well as for multimode fiber with core diameter up to 62.5 μ m. And a reverse voltage of only 5 Volts makes interfacing to a preamplifier easy.



TO-46 Package With Lens

Optical and Electrical Characteristics (25° C Case Temperature)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Responsivity (Fig. 1 & 2) (Table 1)	R	0.35	0.45		A/W	$\lambda=850\text{nm}$
Bandwidth	f_c		1		GHz	$R_L=50\Omega$
Capacitance (Fig. 4)	C		1	2	pF	$f=1\text{MHz}$
Dark Current	I_d		0.4	1	nA	

Operating Conditions: $V_R=5\text{V}$. Fiber: Single-mode to multimode 62.5/125 μ m.

Absolute Maximum Ratings

PARAMETER	SYMBOL	LIMIT
Storage Temperature	T_{stg}	-55 to +125°C
Operating Temperature	T_{op}	-55 to +125°C
Reverse Voltage	V_R	30V
Soldering Temperature (2mm from the case for 10 sec)	T_{sld}	260°C

Thermal Characteristics

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Temperature Coefficient - Dark Current	dI_d/dT_j		5		%/°C

12627.11 1998-02-04



Europe: Tel (46) 8 58 02 45 00 Fax (46) 8 58 02 01 10
Tel (44) 1291 436180 Fax (44) 1291 436771

America: Tel 1-800-96MITEL Fax (613) 592-6909
Asia: Tel (65) 293 5312 Fax (65) 293 8527

Typical Responsivity		
Core Diameter/Cladding Diameter Numerical Aperture		
10/125 μm 0.11	50/125 μm 0.20	62.5/125 μm 0.275
0.45 A/W	0.45 A/W	0.45 A/W

Table 1

