



ALPHA & OMEGA
SEMICONDUCTOR



AON4602

Complementary Enhancement Mode Field Effect Transistor


General Description

The AON4602 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs form a high-speed power inverter, suitable for a multitude of applications. Standard Product AON4602 is Pb-free (meets ROHS & Sony 259 specifications). AON4602L is a Green Product ordering option. AON4602 and AON4602L are electrically identical.


Features

n-channel p-channel

V_{DS} (V) = 20V	-20V	
I_D = 4.2A	-3.4A	($V_{GS} = \pm 4.5V$)
$R_{DS(ON)} < 50m\Omega$	< 90m Ω	($V_{GS} = \pm 4.5V$)
$R_{DS(ON)} < 63m\Omega$	< 120m Ω	($V_{GS} = \pm 2.5V$)
$R_{DS(ON)} < 87m\Omega$	< 160m Ω	($V_{GS} = \pm 1.8V$)



DFN3X2



Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage	V_{DS}	20	-20	V
Gate-Source Voltage	V_{GS}	± 8	± 8	V
Continuous Drain Current ^A	I_D	4.2	-3.4	A
$T_A=70^\circ C$		3.2	-2.7	
Pulsed Drain Current ^B	I_{DM}	15	-15	
Power Dissipation	P_D	1.4	1.7	W
$T_A=70^\circ C$		0.9	1.1	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	-55 to 150	°C

Thermal Characteristics: n-channel

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	70	90	°C/W
Steady-State		100	125	°C/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	63	80	°C/W

Thermal Characteristics: p-channel

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	49	75	°C/W
Steady-State		81	100	°C/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	37	45	°C/W

n-channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	20			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=16\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		1	5	μA
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 8\text{V}$		100	100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	0.4	0.7	1	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	15			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=4.5\text{V}, I_D=4.2\text{A}$ $T_J=125^\circ\text{C}$	41	50		$\text{m}\Omega$
		$V_{GS}=2.5\text{V}, I_D=3.7\text{A}$	58	70		$\text{m}\Omega$
		$V_{GS}=1.8\text{V}, I_D=3.2\text{A}$	52	63		$\text{m}\Omega$
g_{FS}	Forward Transconductance	$V_{DS}=5\text{V}, I_D=4.2\text{A}$		11		S
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.8	1	V
I_S	Maximum Body-Diode Continuous Current			2	2	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=10\text{V}, f=1\text{MHz}$		436		pF
C_{oss}	Output Capacitance			66		pF
C_{rss}	Reverse Transfer Capacitance			44		pF
R_g	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		3		Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=10\text{V}, I_D=4.2\text{A}$		6.2		nC
Q_{gs}	Gate Source Charge			1.6		nC
Q_{gd}	Gate Drain Charge			0.5		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=5\text{V}, V_{DS}=10\text{V}, R_L=2.7\Omega, R_{\text{GEN}}=6\Omega$		5.5		ns
t_r	Turn-On Rise Time			6.3		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			40		ns
t_f	Turn-Off Fall Time			12.7		ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=4\text{A}, dI/dt=100\text{A}/\mu\text{s}$		12.3		ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=4\text{A}, dI/dt=100\text{A}/\mu\text{s}$		3.5		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $\leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

D: The static characteristics in Figures 1 to 6, 12, 14 are obtained using 80 μs pulses, duty cycle 0.5% max.







E: These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$.

The SOA curve provides a single pulse rating.

Rev0 : Jan. 2006

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

p-channel MOSFET Electrical Characteristics ($T=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_{\text{D}}=-250\mu\text{A}, V_{\text{GS}}=0\text{V}$	-20			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=-16\text{V}, V_{\text{GS}}=0\text{V}$ $T_{\text{J}}=55^{\circ}\text{C}$			-1 -5	μA
I_{GSS}	Gate-Body leakage current	$V_{\text{DS}}=0\text{V}, V_{\text{GS}}=\pm 8\text{V}$			± 100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\mu\text{A}$	-0.3	-0.63	-1	V
$I_{\text{D(ON)}}$	On state drain current	$V_{\text{GS}}=-4.5\text{V}, V_{\text{DS}}=-5\text{V}$	-15			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=-4.5\text{V}, I_{\text{D}}=-3.4\text{A}$ $T_{\text{J}}=125^{\circ}\text{C}$		73 102	90 125	$\text{m}\Omega$
		$V_{\text{GS}}=-2.5\text{V}, I_{\text{D}}=-2.5\text{A}$		95	120	$\text{m}\Omega$
		$V_{\text{GS}}=-1.8\text{V}, I_{\text{D}}=-1.5\text{A}$		123	160	$\text{m}\Omega$
g_{FS}	Forward Transconductance	$V_{\text{DS}}=-5\text{V}, I_{\text{D}}=-3.4\text{A}$	4	7		S
V_{SD}	Diode Forward Voltage	$I_{\text{S}}=-1\text{A}, V_{\text{GS}}=0\text{V}$		-0.83	-1	V
I_{S}	Maximum Body-Diode Continuous Current				-2	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=-10\text{V}, f=1\text{MHz}$		540		pF
C_{oss}	Output Capacitance			72		pF
C_{rss}	Reverse Transfer Capacitance			49		pF
R_g	Gate resistance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, f=1\text{MHz}$		12		Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	$V_{\text{GS}}=-4.5\text{V}, V_{\text{DS}}=-10\text{V}, I_{\text{D}}=-3.8\text{A}$		6.1		nC
Q_{gs}	Gate Source Charge			0.6		nC
Q_{gd}	Gate Drain Charge			1.6		nC
$t_{\text{D(on)}}$	Turn-On DelayTime	$V_{\text{GS}}=-4.5\text{V}, V_{\text{DS}}=-10\text{V}, R_{\text{L}}=2.6\Omega, R_{\text{GEN}}=3\Omega$		10		ns
t_r	Turn-On Rise Time			12		ns
$t_{\text{D(off)}}$	Turn-Off DelayTime			44		ns
t_f	Turn-Off Fall Time			22		ns
t_{rr}	Body Diode Reverse Recovery Time	$I_{\text{F}}=-3.8\text{A}, \text{dI/dt}=100\text{A}/\mu\text{s}$		21		ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_{\text{F}}=-3.8\text{A}, \text{dI/dt}=100\text{A}/\mu\text{s}$		7.5		nC

A: The value of R_{0JA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The R_{0JA} is the sum of the thermal impedance from junction to lead R_{0JL} and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The SOA curve provides a single pulse rating.

Rev 0. Jan. 2006

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance