

# Chip Wirewound Inductors

## Molded Type Chip Wirewound Inductors - TRCM Series TRCM Series Wirewound Chip Inductors

### ▶ Preview

Miniaturisation of today's electrical and electronic devices requires component manufacturers to increase the performance of components without increasing footprint. Token TRCM series utilizes wirewound technology that offers wide Pad inductor with the highest SRF carrying capability, highest usable frequency range, and the best Q factor of the narrow pad TREM and TREC series.

The latest wirewound chip inductor TRCM series offers improved performance in the same compact molded case size. These series conform to the RoHS directive and Lead-free. Custom parts are available on request. Token will also produce devices outside these specifications to meet specific customer requirements, please contact our sales for more information.



### A Brief Introduction to the Product :

SMD Inductors CM322522 and CM453232 series are revolutionary, high reliable wire wound components for communication, equipment, instruments, video & audio have been developed in response to the trend toward higher density mounting of inductor parts in electric circuits.

### Materials :

- Ferrite DR core, enamelled copper wire, tinned copper flat, epoxy novolac moldind compound

### Features :

- High resistance to heat and humidity.
- Resistant to mechanical shocks and pressures.
- Accurate dimensions for automatically surface mounted.
- Good heat durability that withstands lead-free compatible reflow soldering conditions.

### Applications :

- Other electronic equipment including HDDs and ODDs.
- Audio-visual equipment including TVs, VCRs and digital cameras.
- Electronic equipment used in onboard automobile equipment including car audio and ECU systems.
- Electronic equipment used in communication infrastructures including xDSL and mobile base stations.

## Configurations & Dimensions (Unit: mm)

Type	A	B	C	D	E	F	G	H
TRCM322522(1210)	$3.2 \pm 0.3$	$2.5 \pm 0.2$	$2.2 \pm 0.2$	$0.4^{+0.1}_{-0}$	$1.9 \pm 0.1$	3.0	1.0	2.0
TRCM453232(1812)	$4.5 \pm 0.3$	$3.2 \pm 0.2$	$3.2 \pm 0.2$	$0.4^{+0.1}_{-0}$	$2.6 \pm 0.1$	4.0	1.5	3.0

## Reel & Packaging (Unit: mm)

TYPE	A	B	C	D	G	N	T
8mm	178	$21.0 \pm 0.8$	$13.0 \pm 0.5$	8	10 max	50 min	14.4 max
12mm	178	$21.0 \pm 0.8$	$13.0 \pm 0.5$	10	14 max	50 min	14.4 max

**▶ TRCM322522 (EIA 1210) - Standard Electrical Characteristics**

Part No.	Inductance (μH)	Q (min)	Test Freq. (MHZ)	SRF (MHz)(min)	DCR (Ω)(max)	IDC (mA)
TRCM322522 - 010J	0.01 ± 5%	15	100	2500	0.13	450
TRCM322522 - 012J	0.012 ± 5%	17	100	2300	0.14	450
TRCM322522 - 015J	0.015 ± 5%	19	100	2100	0.16	450
TRCM322522 - 018J	0.018 ± 5%	21	100	1900	0.18	450
TRCM322522 - 022J	0.022 ± 5%	23	100	1700	0.2	450
TRCM322522 - 027J	0.027 ± 5%	23	100	1500	0.22	450
TRCM322522 - 033J	0.033 ± 5%	25	100	1400	0.24	450
TRCM322522 - 039J	0.039 ± 5%	25	100	1300	0.27	450
TRCM322522 - 047J	0.047 ± 5%	26	100	1200	0.3	450
TRCM322522 - 056J	0.056 ± 5%	26	100	1100	0.33	450
TRCM322522 - 068J	0.068 ± 5%	27	100	1000	0.36	450
TRCM322522 - 082J	0.082 ± 5%	27	100	900	0.4	450
TRCM322522 - R10J	0.1 ± 5%	28	100	700	0.44	450
TRCM322522 - R12J	0.12 ± 5%	30	25.2	500	0.22	450
TRCM322522 - R15J	0.15 ± 5%	30	25.2	400	0.28	450
TRCM322522 - R18J	0.18 ± 5%	30	25.2	400	0.28	450
TRCM322522 - R22J	0.22 ± 5%	30	25.2	350	0.32	450
TRCM322522 - R27J	0.27 ± 5%	30	25.2	320	0.36	450
TRCM322522 - R33J	0.33 ± 5%	30	25.2	300	0.4	250
TRCM322522 - R39J	0.39 ± 5%	30	25.2	250	0.45	450
TRCM322522 - R47J	0.47 ± 5%	30	25.2	220	0.5	450
TRCM322522 - R56J	0.56 ± 5%	30	25.2	180	0.55	450
TRCM322522 - R68J	0.68 ± 5%	30	25.2	160	0.6	450
TRCM322522 - R82J	0.82 ± 5%	30	25.2	140	0.65	450
TRCM322522 - 1R0J	1 ± 5%	30	7.96	120	0.7	400
TRCM322522 - 1R2J	1.2 ± 5%	30	7.96	100	0.75	390
TRCM322522 - 1R5J	1.5 ± 5%	30	7.96	85	0.85	370
TRCM322522 - 1R8J	1.8 ± 5%	30	7.96	80	0.9	350
TRCM322522 - 2R2J	2.2 ± 5%	30	7.96	75	1	320
TRCM322522 - 2R7J	2.7 ± 5%	30	7.96	70	1.1	290
TRCM322522 - 3R3J	3.3 ± 5%	30	7.96	60	1.2	260
TRCM322522 - 3R9J	3.9 ± 5%	30	7.96	55	1.3	250
TRCM322522 - 4R7J	4.7 ± 5%	30	7.96	50	1.5	220
TRCM322522 - 5R6J	5.6 ± 5%	30	7.96	45	1.6	200
TRCM322522 - 6R8J	6.8 ± 5%	30	7.96	40	1.8	180
TRCM322522 - 8R2J	8.2 ± 5%	30	7.96	35	2	170
TRCM322522 - 100J	10 ± 5%	30	2.52	30	2.1	150
TRCM322522 - 120J	12 ± 5%	30	2.52	20	2.5	140
TRCM322522 - 150J	15 ± 5%	30	2.52	20	2.8	130
TRCM322522 - 180J	18 ± 5%	30	2.52	20	3.3	120

Continued on the following page. 

↑ Continued from the preceding page.

Part No.	Inductance ( $\mu$ H)	Q (min)	Test Freq. (MHZ)	SRF (MHz)(min)	DCR ( $\Omega$ )(max)	IDC (mA)
TRCM322522 - 220J	22 $\pm$ 5%	30	2.52	20	3.7	110
TRCM322522 - 270J	27 $\pm$ 5%	30	2.52	20	5	80
TRCM322522 - 330J	33 $\pm$ 5%	30	2.52	17	5.6	70
TRCM322522 - 390J	39 $\pm$ 5%	30	2.52	16	6.4	65
TRCM322522 - 470J	47 $\pm$ 5%	30	2.52	15	7	60
TRCM322522 - 560J	56 $\pm$ 5%	30	2.52	13	8	55
TRCM322522 - 680J	68 $\pm$ 5%	30	2.52	12	9	50
TRCM322522 - 820J	82 $\pm$ 5%	30	2.52	11	10	45
TRCM322522 - 101J	100 $\pm$ 5%	20	0.796	10	10	40
TRCM322522 - 121J	120 $\pm$ 5%	20	0.796	10	11	70
TRCM322522 - 151J	150 $\pm$ 5%	20	0.796	8	15	65
TRCM322522 - 181J	180 $\pm$ 5%	20	0.796	7	17	60
TRCM322522 - 221J	220 $\pm$ 5%	20	0.796	7	21	50
TRCM322522 - 271J	270 $\pm$ 5%	20	0.796	6	28	45
TRCM322522 - 331J	330 $\pm$ 5%	20	0.796	5	34	40
TRCM322522 - 391J	390 $\pm$ 5%	20	0.796	5	36	35
TRCM322522 - 471J	470 $\pm$ 5%	20	0.796	4	40	25

## ▶ TRCM453232 (EIA 1812) - Standard Electrical Characteristics

Part No.	Inductance (μH)	Q (min)	Test Freq. (MHZ)	SRF (MHz)(min)	DCR (Ω)(max)	IDC (mA)
TRCM453232 - 1R0J	1 ± 5%	50	7.96	100	0.5	450
TRCM453232 - 1R2J	1.2 ± 5%	50	7.96	80	0.55	430
TRCM453232 - 1R5J	1.5 ± 5%	50	7.96	70	0.6	410
TRCM453232 - 1R8J	1.8 ± 5%	50	7.96	60	0.65	390
TRCM453232 - 2R2J	2.2 ± 5%	50	7.96	55	0.7	380
TRCM453232 - 2R7J	2.7 ± 5%	50	7.96	50	0.75	370
TRCM453232 - 3R3J	3.3 ± 5%	50	7.96	45	0.8	355
TRCM453232 - 3R9J	3.9 ± 5%	50	7.96	40	0.9	330
TRCM453232 - 4R7J	4.7 ± 5%	50	7.96	35	1	315
TRCM453232 - 5R6J	5.6 ± 5%	50	7.96	33	1.1	300
TRCM453232 - 6R8J	6.8 ± 5%	50	7.96	27	1.2	285
TRCM453232 - 8R2J	8.2 ± 5%	50	7.96	25	1.4	270
TRCM453232 - 100J	10 ± 5%	50	2.52	20	1.6	250
TRCM453232 - 120J	12 ± 5%	50	2.52	18	2	225
TRCM453232 - 150J	15 ± 5%	50	2.52	17	2.5	200
TRCM453232 - 180J	18 ± 5%	50	2.52	15	2.8	190
TRCM453232 - 220J	22 ± 5%	50	2.52	13	3.2	180
TRCM453232 - 270J	27 ± 5%	50	2.52	12	3.6	170
TRCM453232 - 330J	33 ± 5%	50	2.52	11	4	160
TRCM453232 - 390J	39 ± 5%	50	2.52	10	4.5	150
TRCM453232 - 470J	47 ± 5%	50	2.52	10	5	140
TRCM453232 - 560J	56 ± 5%	50	2.52	9	5.5	135
TRCM453232 - 680J	68 ± 5%	50	2.52	9	6	130
TRCM453232 - 820J	82 ± 5%	50	2.52	8	7	120
TRCM453232 - 101J	100 ± 5%	40	0.796	8	8	110
TRCM453232 - 121J	120 ± 5%	40	0.796	6	8	110
TRCM453232 - 151J	150 ± 5%	40	0.796	5	9	105
TRCM453232 - 181J	180 ± 5%	40	0.796	5	9.5	102
TRCM453232 - 221J	220 ± 5%	40	0.796	4	10	100
TRCM453232 - 271J	270 ± 5%	40	0.796	4	12	92
TRCM453232 - 331J	330 ± 5%	40	0.796	3.5	14	85
TRCM453232 - 391J	390 ± 5%	40	0.796	3	16	80
TRCM453232 - 471J	470 ± 5%	40	0.796	3	26	62
TRCM453232 - 561J	560 ± 5%	30	0.796	3	30	50
TRCM453232 - 681J	680 ± 5%	30	0.796	3	30	50
TRCM453232 - 821J	820 ± 5%	30	0.796	2.5	35	30
TRCM453232 - 102J	1000 ± 5%	30	0.252	2.5	40	30

## ▶ TRCM322522, TRCM453232 - Mechanical Performance Test

REQUIREMENTS	CHARACTERISTICS	TEST METHOD(DIS C 5321)
Terminal Strength	No evidence of damage	Terminals shall withstand a pull of 0.5Kgf in a horizonal direction
Vibration	$\Delta L/L$ shall be within $\pm 3\%$ . No evidence of damage	2 hours in each direction of X,Y,Z on p-Board at a frequency range of 10-55-10HZ with 1.5mm amplitude
Dropping	$\Delta L/L$ shall be within $\pm 3\%$ . No evidence of damage	Dropping 1m over the ground of concrete or cement

## ▶ TRCM322522, TRCM453232 - Electrical Performance Test

REQUIREMENTS	CHARACTERISTICS	TEST METHOD(JIS C 5321)
Resistance to Soldering Heat	No evidence of damage $\Delta L/L$ shall be within $\pm 3\%$	Immerse in the solder (H63A) of $260 \pm 5^\circ\text{C}$ for $10 \pm 1$ sec, leave for 2hrs at normal TEMP
Solderability	More than 90% surface to be covered with new soldering	AV100V 60 SEC.
Dielectric with standing voltage	No veridence of breakdown resistor 1000 Mohm and over	DC500V 30 SEC.
Insulation Resistance	No veidence of breakdown, resistor 1000 Mohm and over	DC 500V 30 SEC.

## ▶ TRCM322522, TRCM453232 - Climatic Test

REQUIREMENTS	CHARACTERISTICS	TEST METHOD(JIS C 5321)
LOW TEMP. Characteristics	No evidence of damage, $\Delta L/L$ within $\pm 5\%$ , Q/Q within $\pm 30\%$	Immerse in the solder (H63A) of $260 \pm 5^\circ\text{C}$ for $10 \pm 1$ sec, leave for 2hrs at normal TEMP.
TEMP. Cycling	No evidence of damage, $\Delta L/L$ within $\pm 5$	Keep for 30 min. at TEMP. of $-25^\circ\text{C} \sim +85^\circ$ Cat 5 cycle case of TEMP. change from low to high and V.V.
Temperature Characteristics	$\Delta L/L$ within $\pm 3\%$	$\Delta L/L$ to be measured at the temperature of between $-25^\circ\text{C}$ and $+85^\circ\text{C}$
Moiisture load Characteristics	No evidence of damage, $\Delta L/L$ within $\pm 5\%$ , Q/Q within $\pm 30$	TEMP. $40 \pm 2^\circ\text{C}$ , Humidity 90~95% $96 \pm 2$ hrs, measurements shall be performed after 1~2hrs at normal TEMP..
High TEMP. overload Characteristics	No evidence of damage, $\Delta L/L$ within $\pm 5\%$ , Q/Q within $\pm 30$	Leave for $96 \pm 2$ hrs in a bath of TEMP. $85 \pm 2^\circ\text{C}$ , measurements shall be performed after 1~2hrs at normal TEMP.

## ▶ How to Order

TRCM322522

❶

R10

❷

J

❸

❶ Part Number: TRCM322522, TRCM453232

❷ Inductance

Code	Inductance
R10	0.10 $\mu$ H
1R0	1.00 $\mu$ H
100	10.00 $\times 10^0\mu$ H
101	10.00 $\times 10^1\mu$ H
102	10.00 $\times 10^2\mu$ H

❸ Tolerance

Code	Tolerance
J	5%

*Back to 1st Page - Chip Wirewound Inductors (TRCM)*