



Multistage (Cascade) Series Specifications for greater temperature differentials

Catalog Number	I _{max} (Amps)	TH = 25°C			Dimensions (mm)				
		Q _{max} ⁽¹⁾ (Watts)	V _{max} (Volts)	ΔT _{max} (°C)	A	B	C	D	E ⁽²⁾
2 FC 025 040-7-3	1.45	0.42	0.84	85.9	3.2	3.2	3.9	3.9	3.8
2 FC 025 040-16-8	1.40	1.03	1.96	83.0	4.1	4.1	6.1	6.1	4.2
2 FC 018 050-65-18	0.65	1.19	7.96	91.6	4.9	4.9	9.8	9.8	4.2
2 CP 040 080-7-2	2.0	0.41	0.8	91	3.5	3.5	8	8	7.4
2 CP 040 065-31-17	2.1	3.11	3.8	81	11.5	11.5	15	15	6.6
2 CP 055 065-31-17	4.0	6.04	3.8	81	15	15	20	20	7.2
2 CP 085 100-31-20	5.9	9.74	3.8	77	23	26	30	30	10.7
2 CP 055 065-71-31	4.3	12.65	8.6	85	20	20	30	30	7.2
2 SC 040 050-127-63	2.8	16.05	15.5	83	30	30	30	30	7.1
2 CP 085 065-71-31	10.3	30.22	8.6	85	30	30	44	44	8.9
2 SC 055 045-127-63	6.0	34.51	15.5	83	40	40	40	40	7.5
2 SC 085 065-127-70	9.5	59.25	15.5	81	62	62	62	62	8.9
3 CP 040 065-31-17-7	1.8	1.52	3.8	96	8	8	15	15	9.5
3 CP 040 065-127-71-31	1.8	6.48	15.4	96	15	15	30	30	9.5
3 CP 055 065-71-31-17	3.5	6.53	7.7	97	15	15	30	30	10.4
3 CP 055 065-127-71-31	3.5	12.58	15.4	96	20	20	40	40	10.4
3 CP 085 065-71-31-17	8.4	15.60	7.7	97	22	22	44	44	12.9
4 CP 040 080-31-17-7-2	1.5	0.47	3.8	114	3.5	3.5	15	15	14.0
4 CP 040 080-64-26-11-6	1.4	1.08	6.8	110	4	11	16	23	6.0
4 CP 040 065-71-31-17-7	1.7	1.66	7.9	110	8	8	23	23	12.5
4 CP 055 065-69-29-11-6	3.4	2.68	7.5	112	4.5	14.5	24	33	13.8
4 CP 040 080-127-71-31-17	1.3	2.87	14.6	107	11.5	11.5	30	30	14.0
4 CP 055 065-127-71-31-17	3.1	6.84	14.6	107	15	15	40	40	13.8
5 CP 040 065-127-71-31-17-7	1.6	1.74	14.5	118	8	8	30	30	15.4
5 CP 055 065-127-71-31-17-7	3.0	3.37	14.5	118	10	10	40	40	16.9
6 CP 040 065-127-71-31-17-7-2	1.5	0.63	14.5	131	3.5	3.5	30	30	18.3
6 CP 055 065-127-71-31-17-7-2	3.0	1.22	14.5	131	5	5	40	40	20.1

Center Hole (Annular) Series Specifications

for applications where light or a component must pass through the TEC

Catalog Number	I _{max} (Amps)	TH = 25°C			N	Dimensions (mm)				
		Q _{max} ⁽¹⁾ (Watts)	V _{max} (Volts)	ΔT _{max} (°C)		A	B	C	D ⁽²⁾	E
SH 0.6 -62 -06 (-2) L	1.20	5.01	7.52	67	62	12.3	11.3	13.4	2.7	2.0
SH 0.6 -62 -05 (-2) L	1.50	6.27	7.52	67	62	12.3	11.3	13.4	2.4	2.0
SH 0.65 -62 -04 (-2) L	2.00	8.36	7.52	67	62	12.3	11.3	13.4	2.2	2.0
SH 0.8 -26 -05 L	2.6	4.9	3.9	67	28	14.7	10.3	14.7	3.1	4.4
SH 1.0 -23 -06 L	3.0	4.7	2.8	67	23	15	15	15	3.6	7.2
SH 1.0 -95 -06 L	3.0	19.3	11.5	67	95	30	30	30	3.6	14.5
SH 1.0 -23 -05 L	3.9	6.0	2.8	67	23	15	15	15	3.2	7.2
SH 1.0 -95 -05 L	3.9	25.1	11.5	67	95	30	30	30	3.2	14.5
SH 1.4 -15 -10 L	3.9	3.9	1.8	70	15	14	14	14	4.7	5.1
SH 1.4 -69 -10 L	3.9	18.1	8.4	70	69	30	30	30	4.7	3.6
SH 1.4 -125 -10 L	3.9	32.9	15.2	70	125	40	40	40	4.7	4.7
SH 1.4 -15 -06 L	6.0	6.1	1.8	67	15	14	14	14	3.8	5.1
SH 1.4 -69 -06 L	6.0	27.9	8.4	67	69	30	30	30	3.8	3.6
SH 1.4 -125 -06 L	6.0	50.7	15.2	67	125	40	40	40	3.8	4.7
SH 1.4 -15 -045 L	8.5	8.1	1.8	67	15	14	14	14	3.3	5.1
SH 1.4 -69 -045 L	8.5	37.3	8.4	67	69	30	30	30	3.3	3.6
SH 1.4 -125 -045 L	8.5	67.7	15.2	67	125	40	40	40	3.3	4.7
SH 2 -20 -10 L	9.0	12.2	2.4	70	20	30	30	30	5.6	13
SH 2 -20 -06 L	14.0	18.9	2.4	67	20	30	30	30	4.6	13
RH 1.4 -14 -10 L	3.9	3.7	1.7	70	14	26	26	26	4.7	14
RH 1.4 -32 -10 L	3.9	8.4	3.9	70	32	44	55	55	4.7	27
RH 1.4 -14 -06 L	6.0	5.7	1.7	67	14	26	26	26	3.8	14
RH 1.4 -32 -06 L	6.0	12.9	3.9	67	32	44	55	55	3.8	27
RH 1.4 -14 -045 L	8.5	7.6	1.7	67	14	26	26	26	3.3	14
RH 1.4 -32 -045 L	8.5	17.3	3.9	67	32	44	55	55	3.3	27
RH 2 -10 -10 L	9.0	6.1	1.2	70	10	29	29	29	5.6	13
RH 2 -10 -06 L	14.0	9.4	1.2	67	10	29	29	29	4.6	13

5976646 0000357 881

1040 Spruce Street
Trenton, NJ 08648 USA

TEL (609) 393-4178
FAX (609) 393-9461