


JKL PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF22160-24B	LCD HIGH OUTPUT WHITE 8400°K RGB	800 @ 0°C	370	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
B DIM LINE CORRECT. AND 160+/-5.0 TO 160+/-3.0 A LEAD LENGTH TO 17±3 RELEASED			DRAWN BY L. WENGSTROM		APPV'D BY DATE FD 10/17/00		SIZE A		FSCM NO. 55335		DRAWING NO. BF22160-24B	
REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/29/00		REVISION DATE 10/17/00		REV. NO. B SHEET 1 OF 1	