






10 TAP SURFACE MOUNT AND AUTO-INSERTABLE DDMs

UPGRADED SERIES




- LEADING AND TRAILING EDGE PRECISION
- AVAILABLE WITH SURFACE MOUNT GULL WING LEADS
- AUTOMATICALLY INSERTABLE DIP PACKAGE
- 10 EQUALLY SPACED TAPS
- TTL BUFFERED
- 14 PIN INDUSTRY STANDARD PINOUT




Part Number	Total Delay (ns)	Tap Delay (ns)	Rise Time (ns MAX)
PE-24107	25.0	**2.5	3.0
PE-24108	30.0	3.0	3.0
PE-24110	40.0	4.0	3.0
PE-24112	50.0	5.0	3.0
PE-24113	60.0	6.0	3.0
PE-24114	75.0	7.5	3.0
PE-24115	100.0	10.0	3.0
PE-24116	125.0	12.5	4.0
*PE-24117	150.0	15.0	4.0
*PE-24118	200.0	20.0	4.0

Delay Tolerance: $\pm 2\text{ns}$ or $\pm 5\%$ (whichever is greater) @ $V_{CC}=5.0\text{V}$ $T=25^\circ\text{C}$ No Load
 Tap Delay is referenced to the input. *These parts available with leading edge precision only.
 ** The time delay at the first and second tap of PE-24107 equals 5.0 ns.


BASIC DIP PACKAGE⁽⁴⁾



THRU HOLE



GULL WING



LEAD CO-PLANARITY $\pm .002''$

Notes:

1. All dip Lead dimensions are .130 X .010 X .020 inches.
2. All lead length tolerances are $+.020/-0.010$ inches except where specified.
3. All tolerances (except lead length) are $\pm .010$ inches except where indicated.
4. Pin #1 identified by a white dot on top surface.
5. All MAX length tolerances not inclusive of mold stacking offset or gate flash.

Pulse Engineering, Inc.


P.O. BOX 12235, SAN DIEGO, CA 92112 (619) 268-2400

9000-3865

892-2



10 TAP SURFACE MOUNT AND AUTO-INSERTABLE DDM'S



D.C. ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITION	MIN.	MAX.	UNITS	
ABSOLUTE MAXIMUM RATINGS					
V_{CC}	Supply Voltage		+7.0	Volts	
V_{IH}	High Level Input Voltage		+5.5	Volts	
T_A	Operating Temperature Range	Free Air	0	+70	$^\circ$ C
	Storage Temperature Range	Free Air	-55	+125	$^\circ$ C

RECOMMENDED OPERATION CONDITIONS

V_{CC}	Supply Voltage		4.75	5.25	Volts		
V_{IH}	High Level Input Voltage (Logic 1)		2		Volts		
V_{IL}	Low Level Input Voltage (Logic 0)	$V_{CC} = \text{Min.}$.8	Volts		
I_I	Input Current (Maximum @ V_{IH} Max.)	$V_{CC} = \text{Max.}$	$V_{IH} = 5.50$	1	mA		
I_{IH}	High Level Input Current	$V_{CC} = \text{Max.}$	$V_{IH} = 2.70$	100	μ A		
I_{IL}	Low Level Input Current	$V_{CC} = \text{Max.}$	$V_{IL} = 0.5$	-4	mA		
V_{OH}	High Level Output Voltage	$V_{CC} = \text{Min.}$	$V_{IH} = 2.0V$	$I_{OH} = -1mA$	2.7	Volts	
V_{OL}	Low Level Output Voltage	$V_{CC} = \text{Min.}$	$V_{IL} = 0.8V$	$I_{OL} = 20mA$.5	Volts	
I_{OS}	Short Circuit Output Current	$V_{CC} = \text{Max.}$	(1 Output \leq 1 Sec.)		-40	-100	mA
N	Normalized Fan-out (per device)	$V_{CC} = \text{Max.}$			20	Loads	
N	Normalized Fan-out (per output)	$V_{CC} = \text{Max.}$			10	Loads	
I_{CCH}	Supply Current High Level Output	$V_{CC} = \text{Max.}$	$V_{IH} = 3.2$		60	mA	
I_{CCL}	Supply Current Low Level Output	$V_{CC} = \text{Max.}$	$V_{IL} = 0$		120	mA	

Performance warranty of products offered on data sheet 892-2 is limited to the parameters specified. Data is subject to change without notice.
 Copyright 1990, Pulse Engineering, Inc.

DIRECT SALES OFFICES

SAN JOSE
 (408) 279-3336
 FAX: 408-279-3460

CHICAGO
 (708) 297-0111
 FAX: 708-297-0030

ATLANTA
 (404) 448-0526
 FAX: 404-448-3970

ENGLAND
 Tel. 44 81 669 7720
 FAX: 44 81 669 7732

IRELAND
 Tel. 353 93 24107
 FAX: 353 93 24883

SAN DIEGO
 (619) 268-2400
 FAX: 619-268-2515

BOSTON
 (508) 670-5738
 FAX: 508-670-5742

HONG KONG
 Tel. 8524271272
 FAX: 8524805974

FRANCE
 Tel. 33 1 60 19 11 11
 FAX: 33 1 60 19 09 10

GERMANY
 Tel. 49 89 96 3046
 FAX: 49 89 96 6626

Pulse Engineering, Inc.

P.O. BOX 12235, SAN DIEGO, CA 92112 (619) 268-2400

892-2

10/90