PIN RECEPTACLES
for 0,38 - 0,64 diameter pins

0669



0669-0-15-XX-30-XX-10-0
Solder mount in 1,52 min. mounting hole
Also available on 16mm wide carrier tape: 1,700 parts per 330mm reel.
Order as: 0669-0-57-XX-30-XX-10-0

0670



0670-0-15-XX-30-XX-10-0
Solder mount in 1,52 min. mounting hole

0673



0673-0-15-XX-30-XX-10-0
Surface Mount

0666



0666-0-15-XX-32-XX-10-0
Solder mount in 1,63 min. mounting hole
Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel.
Order as: 0666-0-57-XX-32-XX-10-0

0341



0341-0-15-XX-30-XX-10-0
Solder mount in 1,85 mounting hole
Also available on 12mm wide carrier tape: 1,400 parts per 330mm reel.
Order as: 0341-0-57-XX-30-XX-10-0

0252



0252-0-15-XX-32-XX-10-0
Hex press-fit in 1,45 plated thru hole

0678



0678-0-15-XX-32-XX-10-0
Press-fit in 1,45 mounting hole

0676



0676-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

0697



0697-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

0668



0668-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

0253/1033



Basic Part Number	Length L	Depth N
0253-0	4,39	3,76
1033-0	5,16	4,11

XXX3-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: ±0,13
DIAMETERS: ±0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:
01 5,08µm TIN/LEAD OVER NICKEL
◇ **80** 5,08µmTIN OVER NICKEL (RoHS)
◇ **15** 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:
02 2,54µm TIN/LEAD OVER NICKEL
◇ **84** 2,54µm TIN OVER NICKEL (RoHS)
◇ **27** 0,76µm GOLD OVER NICKEL (RoHS)

RoHS 2002/95/EC

SELECT CONTACT
#30 or #32 CONTACT (DATA ON PAGE 219)