

# Pro Flex® Rubber Extension Cords

3-Conductor Grounded • Type SJ • 60°C • 300 Volts

CATALOG NUMBER	NO. OF COND.	AWG SIZE	LENGTH OF CORD (FT)	COLOR OF JACKET	POWER RATING			NEMA CONFIG.	PKG. PER CTN.	WT./ UNIT LBS	WT./ CTN. LBS	UPC CODE
					VOLTS	AMPS	WATTS					
06610.63.01	3	16	10	Black	125	13	1625	5-15P/5-15R	24	0.7	17	079407066100
06625.63.01	3	16	25	Black	125	13	1625	5-15P/5-15R	24	1.7	40	079407066254
06911.63.01	3	14	25	Black	125	15	1875	5-15P/5-15R	6	2.3	14	079407069118



**Product Construction:**

**Conductor:**

- 16 AWG through 14 AWG stranded bare copper per ASTM B-174

**Insulation:**

- Premium-grade, color-coded EPDM

**Jacket:**

- CPE; black
- Temperature: 60°C
- Voltage rating: 300 volts

**Applications:**

- Floor polishers
- Sanders

**Features:**

- General use indoor cord
- 3-conductor grounded

**Industry Approvals:**

- UL Listed
- OSHA Acceptable for indoor use

# Coiled Power Tool Extension Cords and Power Supply Cords

2 and 3 Conductor • Type SJT • 60°C • 300 Volts

CATALOG NUMBER	NO. OF COND.	AWG SIZE	LENGTH OF CORD (FT)	COLOR OF JACKET	POWER RATING			NEMA CONFIG.	PKG. PER CTN.	WT./ UNIT LBS	WT./ CTN. LBS	UPC CODE
					VOLTS	AMPS	WATTS					
06014.60.04	3	16	10	Orange	125	13	1625	5-15P/5-15R	10	1.1	11	079407060146
02551.70.01	3	16	12	Black	125	15	1875	5-15P	10	1.1	11	079407025510



**Product Construction:**

**Conductor:**

- 16 AWG stranded bare copper per ASTM B-174

**Insulation:**

- Premium-grade, color-coded PVC

**Jacket:**

- PVC; orange or black
- Voltage rating: 300 volts

**Applications:**

- Workshop and tool bench use

**Features:**

- Coiled cord expands from 3' to 10' or 12'
- Right-angle plug helps prevent the cord from being pulled from the socket

**Features (cont'd.):**

- 06014.60.04 and 02551.70.01 are 3-conductor grounded

**Industry Approvals:**

- UL Listed
- OSHA Acceptable

# Power Supply Replacement Cords with Switch

3-Conductor Grounded • Type SJ • 60°C • 300 Volts

CATALOG NUMBER	NO. OF COND.	AWG SIZE	LENGTH OF CORD (FT)	COLOR OF JACKET	POWER RATING			NEMA CONFIG.	SWITCH SPEED	PKG. PER CTN.	WT./ UNIT LBS	WT./ CTN. LBS	UPC CODE
					VOLTS	AMPS	WATTS						
02332.70.01	3	16	10	Black	125	10	1250	5-15P	1 Speed (On/Off)	25	0.9	22	079407023325
02333.70.01	4	16	10	Black	125	10	1250	5-15P	2 Speed (On/High/Low)	25	0.9	22	079407023332

**Product Construction:**

**Conductor:**

- 16 AWG stranded bare copper per ASTM B-174

**Insulation:**

- Premium-grade, color-coded EPDM

**Jacket:**

- CPE; black

**Applications:**

- For replacement use
- For fan replacements

**Features:**

- Switch
- Straight plug
- Conductor stripped 5/8"
- Jacket removed 2"

**Industry Approvals:**

- UL Listed
- CSA

