

Features

- 22.4 dB Gain at 150 MHz
- 23 dBm P1dB at 150 MHz
- 42 dBm Output IP3 at 150 MHz
- 2.2 dB NF at 150 MHz
- MTTF > 100 Years
- Single Supply
- Minimal External Components

Description

The ASF255, a IF gain block amplifier MMIC, has a high linearity, high gain, and high efficiency over a wide range of frequency, being suitable for use in both receiver and transmitter of telecommunication systems up to 3 GHz. It has an active bias network for stable current over temperature and process variation. The amplifier is available in an SOT-89 package and passes through the stringent DC, RF, and reliability tests



Package Style: SOT-89

Typical Performance

Parameters	Units	Typical						
		70	150	300	450	900	1500	3000
Frequency	MHz	70	150	300	450	900	1500	3000
Gain	dB	22.4	22.4	22.2	21.9	21.0	22.1	22.1
S11	dB	-15.5	-18	-18	-16	-11	-18	-18
S22	dB	-15.5	-20	-20	-20	-13	-20	-20
Output IP3 ¹⁾	dBm	39	42	42	40	38	40	40
Noise Figure	dB	2.2	2.2	2.3	2.3	2.3	2.2	2.2
Output P1dB	dBm	22.5	23.0	23.0	23.0	22.5	22.0	22.0
Current	mA	102	102	102	102	102	90	90
Device Voltage	V	5	5	5	5	5	4.5	4.5

1) OIP3 is measured with two tones at an output power of +8 dBm/tone separated by 1 MHz.

Application Circuit

- 50 ~ 1000 MHz (5 V)
- 50 ~ 1000 MHz (4.5 V, 90 mA)
- 50 ~ 2150 MHz (5 V)
- 50 ~ 1000 MHz (6 V)

Product Specifications


Parameters	Units	Min	Typ	Max
Testing Frequency	MHz		150	
Gain	dB		22.4	
S11	dB		-18	
S22	dB		-20	
Output IP3	dBm		42	
Noise Figure	dB		2.2	
Output P1dB	dBm		23	
Current	mA		102	
Device Voltage	V		5	

Absolute Maximum Ratings

Parameters	Rating
Operating Case Temperature	-40 to +85°C
Storage Temperature	-40 to +150°C
Device Voltage	+6 V
Operating Junction Temperature	+150°C
Input RF Power (Continuous)	20 dBm

* Please find the max. input power data from http://www.asb.co.kr/pdf/Maximum_Input_Power_Analysis.pdf

Pin Configuration



Pin No.	Function
1	RF IN
2	GND
3	RF OUT / Bias

APPLICATION CIRCUIT


50 ~ 1000

+5 V


Frequency (MHz)	70	150	300	450	900
Magnitude S21 (dB)	22.4	22.4	22.2	21.9	21.0
Magnitude S11 (dB)	-15.5	-18	-18	-16	-11
Magnitude S22 (dB)	-15.5	-20	-20	-20	-13
Output P1dB (dBm)	22.5	23.0	23.0	23.0	22.5
Output IP3 ¹⁾ (dBm)	39	42	42	40	38
Noise Figure (dB)	2.2	2.2	2.3	2.3	2.3
Device Voltage (V)	5	5	5	5	5
Device Current (mA)	102	102	102	102	102

1) OIP3 is measured with two tones at an output power of +8 dBm/tone separated by 1 MHz.





Schematic



Board Layout (FR4, 40x40 mm², 0.8T)



S-parameters & K-factor



APPLICATION CIRCUIT


50 ~ 1000

+4.5 V, 90 mA


Frequency (MHz)	70	150	300	450	900
Magnitude S21 (dB)	22.2	22.1	21.9	21.7	20.8
Magnitude S11 (dB)	-15.5	-18	-18	-16	-11
Magnitude S22 (dB)	-15.5	-20	-20	-20	-13
Output P1dB (dBm)	21.5	22.0	22.0	22.0	21.0
Output IP3 ¹⁾ (dBm)	37.5	40.0	40.5	38.0	36.0
Noise Figure (dB)	2.2	2.2	2.3	2.3	2.3
Device Voltage (V)	4.5	4.5	4.5	4.5	4.5
Device Current (mA)	90	90	90	90	90

1) OIP3 is measured with two tones at an output power of +8 dBm/tone separated by 1 MHz.





Schematic



Board Layout (FR4, 40x40 mm², 0.8T)



S-parameters & K-factor



APPLICATION CIRCUIT


50 ~ 2150

+5 V


Frequency (MHz)	50	1000	2150
Magnitude S21 (dB)	18.2	18.4	18.1
Magnitude S11 (dB)	-8	-10	-14
Magnitude S22 (dB)	-8	-17	-7
Output P1dB (dBm)	21.5	21.5	20.0
Output IP3 ¹⁾ (dBm)	38	37	34
Noise Figure (dB)	2.5	2.6	3.0
Supply Voltage (V)	5	5	5
Current (mA)	102	102	102

1) OIP3 is measured with two tones at an output power of +5 dBm/tone separated by 1 MHz.




Schematic



Board Layout (FR4, 40x40 mm², 0.8T)



S-parameters & K-factor



APPLICATION CIRCUIT


50 ~ 1000

+6 V


Frequency (MHz)	70	150	300	450	900
Magnitude S21 (dB)	22.9	22.8	22.7	22.4	21.4
Magnitude S11 (dB)	-15	-18	-18	-15	-10
Magnitude S22 (dB)	-15	-20	-20	-18	-11
Output P1dB (dBm)	24	24.5	24.5	24.5	24.5
Output IP3 ¹⁾ (dBm)	39.5	42.5	42	40.5	38.5
Noise Figure (dB)	2.4	2.4	2.5	2.5	2.5
Device Voltage (V)	6	6	6	6	6
Device Current (mA)	123	123	123	123	123

1) OIP3 is measured with two tones at an output power of +8 dBm/tone separated by 1 MHz.

Schematic



Board Layout (FR4, 40x40 mm², 0.8T)



S-parameters & K-factor

