

SSV SERIES

85°C 4.6mm MAX Height, Lead Free Reflow Soldering.

◆FEATURES

- Case Dia ϕ 4~ ϕ 6.3mm.
- Lead free reflow soldering is available.
- Available for high density mounting.
- RoHS compliance.



◆SPECIFICATIONS


Items	特 性 Characteristics																											
Category Temperature Range	-40~+85°C																											
Rated Voltage Range	4~50V.DC																											
Capacitance Tolerance	±20% (20°C, 120Hz)																											
Leakage Current(MAX)	I=0.01CV or 3 μ A whichever is greater. (After 2 minutes application of rated voltage) I=Leakage Current(μ A) C=Rated Capacitance(μ F) V=Rated Voltage(V)																											
Dissipation Factor(MAX) (tan δ)	<table border="1"> <tr> <td>Rated Voltage (V)</td> <td>4</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>(20°C, 120Hz)</td> </tr> <tr> <td>tan δ</td> <td>0.45</td> <td>0.30</td> <td>0.24</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.14</td> <td></td> </tr> </table>	Rated Voltage (V)	4	6.3	10	16	25	35	50	(20°C, 120Hz)	tan δ	0.45	0.30	0.24	0.19	0.16	0.14	0.14										
Rated Voltage (V)	4	6.3	10	16	25	35	50	(20°C, 120Hz)																				
tan δ	0.45	0.30	0.24	0.19	0.16	0.14	0.14																					
Endurance	After applying rated voltage with rated ripple current for 1000 hrs at 85°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±25% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 250% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>	Capacitance Change	Within ±25% of the initial value.	Dissipation Factor	Not more than 250% of the specified value.	Leakage Current	Not more than the specified value.																					
Capacitance Change	Within ±25% of the initial value.																											
Dissipation Factor	Not more than 250% of the specified value.																											
Leakage Current	Not more than the specified value.																											
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <tr> <td>Rated Voltage (V)</td> <td>4</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>(120Hz)</td> </tr> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>7</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>Z(-40°C)/Z(20°C)</td> <td>15</td> <td>8</td> <td>8</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td></td> </tr> </table>	Rated Voltage (V)	4	6.3	10	16	25	35	50	(120Hz)	Z(-25°C)/Z(20°C)	7	4	3	2	2	2	2		Z(-40°C)/Z(20°C)	15	8	8	4	4	3	3	
Rated Voltage (V)	4	6.3	10	16	25	35	50	(120Hz)																				
Z(-25°C)/Z(20°C)	7	4	3	2	2	2	2																					
Z(-40°C)/Z(20°C)	15	8	8	4	4	3	3																					

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency (Hz)	60(50)	120	500	1k	10k \leq
0.1~1 μ F	0.50	1.00	1.20	1.30	1.50
2.2~4.7 μ F	0.65	1.00	1.20	1.30	1.50
10~47 μ F	0.80	1.00	1.20	1.30	1.50
100~220 μ F	0.80	1.00	1.10	1.15	1.20

◆MARKING



◆PART NUMBER

