



REVISIONS	
ISSUE	CHANGES
0	ER 6381 26 AUG 68 A/E
1	CN 7132 A A.M. 14 APRIL 69
2	CN 7564 C R.W.V. 28 MAY 69
3	CN 12197 A U.G.L. 30 APR 73
4	CN 15772 A JHP 4 MAY 76
5	CN 25100 C GL 9 SEP 83

- NOTES:
- FOR USE WITH RG-9, 214/U CABLES.
 - FOR CABLE INSTRUCTIONS SEE CP-209A
 - FOR CABLE TRIMMING USE KTJ-24 & KTD-81.
 - FOR CRIMPING USE DE SIZE 04.

ITEM	REQ'D	DESCRIPTION	DRAWING NO.
12	1	COUPLING NUT	
11	1	GASKET	
10	1	C-RING	
9	1	TNC CRIMP CONTACT M	A-59-31-1-M07
8	1	INSULATOR	
7	1	WASHER	
6	1	K-GRIP	S-89-35-1-MC7
5	1	GASKET	571-3-M99
4	1	GLAND	S-89-35-9-MC7
3	1	BODY ASSEMBLY	
2	1	K-GRIP SLEEVE	S-89-24-2-MC7
1	1	CLAMP NUT	S-89-35-5-MC7

REF:	
FINISH	
SPEC.	KER 10004
MATL.	
SPEC.	
TNC PLUG	
DRAWN A/E	DATE 26 AUG 68
APPR. EGR	DATE 26 AUG 68
KINGS ELECTRONICS 40 MARBLEDALE ROAD TUCKAHOE, N. Y. 10707	
KA-59-131	

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30'	2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.	3. NO FILLETS PERMITTED.
	4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
	5. ALL DIMENSIONS PRIOR TO PLATING.

SD!