



Material:

- Plug: YUS-06 8P8C 50μ"
- Conductor:
 - Wire: Cat.6 PIMF STR 26AWG
 - Bare Copper 26AWG 7/0.16±0.015MM
- Insulator:
 - Thickness Min. at any point: 0.2MM
 - Thickness Max. Avg.: 0.35MM
 - Diameter: 1.05±0.06MM
- Jacket PVC:
 - Thickness Min. at any point: 0.50MM
 - Thickness Max. Avg.: 0.60MM
 - Diameter: 6.1±0.02MM

PA/R	PINOUT		
	P1(T568B)	WIRE	P2(T568B)
1	1	WHT	1
	2	ORG	2
	3	WHT	3
2	6	GRN	6
	4	BLU	4
3	5	WHT	5
	7	WHT	7
4	8	BRN	8

Ⓜ = Assmann logo



ITEM NO.
A-MCSSP60005-R

TITLE
 Cat.6 SFTP Patch Cable - 8P8C 50μ", Grey, 0.5 Meter

ASSMANN
 Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 ©Copyright 2010 by Assmann Electronic Components
 All International Rights Reserved