# BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#:

Description:

Heat Sink Type: Custom Pin Fin Heat Sink Attachment: N/A

Equivalent Part Number: N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low

ATS015015021-PF-4T

15.00 x 15.00 x 21.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

· Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	9.37 °C/W	7.7 °C/W	6.8 °C/W	6.1 °C/W	5.7 °C/W	5.3 °C/W	5 °C/W
	Ducted Flow	6.9	5.9	5.3	4.9	4.5	4.3	4.1

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
riha	15.00 mm	15.00 mm	21.00 mm	15 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal p application</li> <li>ATS resent performant</li> <li>ATS certification</li> </ul>	n D is fin tip to fin tip performance data are n. rves the right to upd nce. ies that this heat sin	e provided for referent	m of the base to the nce only. Actual per ducts without notice 6-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@gats.com or www.gats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA