# BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#:

Description:

Heat Sink Type: Custom Pin Fin Heat Sink Attachment: N/A

Equivalent Part Number: N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low

ATS015015009-PF-4H

15.00 x 15.00 x 9.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

• Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

### **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 21.94 °C/W          | 17.8 °C/W           | 15.5 °C/W           | 14 °C/W             | 12.8 °C/W           | 11.9 °C/W           | 11.2 °C/W           |
|                    | Ducted Flow   | 14.4                | 12.1                | 10.7                | 9.8                 | 9                   | 8.4                 | 8                   |

## **Product Detail**

| Schematic Image                               | Dimension A   | Dimension B  | Dimension C                                    | Dimension D  | ТІМ                | Finish         |
|---|---|--|--|--|--------------------|----------------|
| alla  | 15.00 mm  | 15.00 mm   | 9.00 mm  | 15 mm  | N/A                | BLACK-ANODIZED |
| Image above is for illustration purpose only. | <ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal p<br/>application</li> <li>ATS resent<br/>performant</li> <li>ATS certifier</li> </ul> | n <b>D</b> is fin tip to fin tip<br>performance data are<br>n.<br>rves the right to upda<br>nce. | e provided for refere<br>ate or change its pro | m of the base to the<br>nce only. Actual perf<br>ducts without notice<br>i-6 and REACH com<br>ble. | formanc<br>to impr | e may vary by  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA