

# Extended Temp High Reliability Crystal



Model: FXA5032\_G Series

RoHS Compliant

Rev. 2/27/2009

Page 1 of 2

[http://www.foxonline.com/need\\_a\\_sample.htm](http://www.foxonline.com/need_a_sample.htm)



## FEATURES

- Meets AEC-Q200 Requirements
- 1.3mm Height
- Tape and Reel (1,000 pcs. STD)

• PART NUMBER <a href="#">Learn More</a> - Internet Required		
Part Number	Model Number	Frequency Range (MHz)
419AG-Frequency-xxxxx	FXA5032AG	8.000 ~ 40.000 MHz
419BG-Frequency-xxxxx	FXA5032BG	8.000 ~ 40.000 MHz

• STANDARD SPECIFICATIONS	
PARAMETERS	MAX (unless otherwise noted)
Frequency	8.000 ~ 40.000 MHz
Frequency Tolerance @ 25°C	±30 PPM, ±50 PPM
Frequency Stability @ 25°C	
-40 ~ +125°C	±100 PPM
-40 ~ +85°C	±50 PPM
Temperature Range	
Operating (TOPR)	-40°C ~ +125°C
Storage (TSTG)	-40°C ~ +125°C
Shunt Capacitance (Co)	5pF
Load Capacitance (CL)	10pF~Series
Drive Level	100µW
Aging per year	±5 PPM
Maximum Soldering Temp / Time	260°C / 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au
Seal Method	Glass

See dimensional drawings on page 2.

Frequency Range (MHz)	Operating Mode	Max ESR Ω
8.000 ~ 9.999999	Fundamental	300
10.000 ~ 15.999999	Fundamental	60
16.000 ~ 40.000000	Fundamental	50

Note: Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, etc. may vary.

The above specifications, having been carefully prepared and checked, are believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

# Extended Temp High Reliability Crystal



Model: FXA5032\_G Series


RoHS Compliant

Rev. 2/27/2009

Page 2 of 2

[http://www.foxonline.com/need\\_a\\_sample.htm](http://www.foxonline.com/need_a_sample.htm)

Need a Sample®



## • TAPE SPECIFICATIONS (millimeters)

MODEL	A	B	C	D	E	F	STD Reel QTY
FXA5032_G	Ø1.5	4.0	8.0	5.5	12.0	1.65	1,000

## • REEL SPECIFICATIONS (millimeters)

MODEL	G	H	I	J	K	L	M
FXA5032_G	2.0	Ø13	Ø21	Ø57	Ø178	13.0	1.6

