

CUS1500M-12 New Product



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	CUS-M
<b>Status</b>	Production
<b>Feature</b>	for Medical instruments
<b>Option</b>	
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 340V
Efficiency	85% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.2 to 14.4V
Maximum Output Current	125A
Maximum Output Power	1500W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	127mm Nom.
Height(H)	63mm Nom.
Depth(D)	261mm Nom.
Weight	3000g Typ.

Other	
Operating Temp. Range	-20 to 60°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1
	CSA60950-1
	EN60950-1
	UL62368-1
	CSA62368-1
	EN62368-1
	ES60601-1 3rd Edition
Safety Standard(Conformed)	CSA C22.2 No.60601-1 3rd Edition
	EN60601-1 3rd Edition
	EN62477-1 (OVCIII)
Safety Standard(Conformed)	Den-an Appendix 12

