



| REV. | REVISIONS REC. | REV. | REVISIONS REC.                  |
|------|----------------|------|---------------------------------|
| 1    | {H1}:5.9-->6.4 | 4    | SHAPE MODIFY AND {K}:17.9->19.8 |
| 2    | SHAPE MODIFY   | 5    | CANCEL {Q},{K}.                 |
| 3    | SHAPE MODIFY   |      |                                 |

|                       |           |              |                |         |                          |                   |      |
|-----------------------|-----------|--------------|----------------|---------|--------------------------|-------------------|------|
| DRAWN & DRAFTED BY    | S.SOOKSAN | TOLERANCES   |                | ANGLE:  | TITLE: EF16-K-H-9P-P1628 |                   |      |
|                       |           | 0<L≤4 ±0.1   | pin pitch ±0.2 | ±1°     | BOBBIN MATERIAL:         | UL REC.           |      |
| CHECKED & APPROVED BY | ANDY LIAO | 4<L≤16 ±0.2  |                | UNIT:   | PHENOLIC PM9820          | UL 94V-0          |      |
|                       |           | 16<L≤63 ±0.3 |                | ORIGIN: | PIN MATERIAL:            | PIN TENSION LOAD: |      |
|                       |           |              |                | TH      | CP WIRE                  | 1.5KG MIN         |      |
|                       |           |              |                |         | DATE:                    | DRAWING NO.       | REV. |
|                       |           |              |                |         | APR.01 '2003             | P-1628            | 5    |